Mobil

FAXAM™ 32

Mobil Industrial , Russia

Paraffinic Process and Flushing Oil

Product Description

FAXAM™ 32 is paraffinic process oil that can be used in a wide variety of industrial and process oil applications. FAXAM 32 can be used as a lubricant in non-critical applications, where oil operating conditions are moderate and there are no requirements for anti-wear or extreme pressure additives. As process oils, their physical characteristics make them suitable for use as a diluent or carrier oil in the manufacture of products such as lubricating oil additives, paper defoamants, seals, carbon paper, and other chemical formulations. FAXAM 32 can be used as a flushing oil for cleaning lubrication systems.

Features and Benefits

- light colour
- low odour
- good solubility characteristics
- good low temperature properties

Applications

- As a flushing oil in circulating systems
- As a carrier oil in formulations requiring good solvency
- As lubricant in less critical systems, where operating conditions are moderate and anti-wear and extreme pressure additives are not required.

Typical Properties

FAXAM	32
ISO Viscosity Grade	32
Colour, ASTM D1500	1.0
Kinematic Viscosity @40°C, ASTM D445	32
Viscosity Index, ASTM D2270	100
Flash Point, °C, ASTM D92	210
Pour Point, °C, ASTM D97	-12

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2019
ExxonMobil Lubricants & Specialties Europe, подразделение ExxonMobil Petroleum & Chemicals BVBA. Настоящая информация относится только к продуктам, поставляемым в Европу, включая Турцию, и страны бывшего Советского Союза.

ООО «Мобил Ойл Лубрикантс» : 123242, Москва, Новинский бульвар, д.31

Вы всегда можете связаться с нами по вопросам, касающихся продуктов Mobil, а также сервисных услуг: https://www.mobil.ru/ru-ru/contact-us-technical

+ 7 (495) 232 22 23

Указанные значения показателей являются типичными для результатов, лежащих в пределах нормальных производственных допусков, но не являются составной частью спецификации или норм. На обычном производстве и при изготовлении на разных заводах возможны отклонения, которые не влияют на эксплуатационные характеристики. Содержащаяся здесь информация может быть изменена без уведомления. Не все продукты могут быть доступны на местном рынке. За дополнительной информацией обращайтесь к местному представителю ExxonMobil или посетите www.exxonmobil.com

ExxonMobil включает в себя множество аффилированных и дочерних компаний, многие из которых содержат в своем наименовании Esso, Mobil или ExxonMobil. Ничто в настоящем документе не подразумевает отмену или преобладания над корпоративной независимостью местных организаций. Ответственность и отчетность за действия на местах остаются за местными аффилированными организациями ExxonMobil.

ExxonMobil

Exxon Mobil Esso XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved