

**Prowaxx™ 1274 SW**

ExxonMobil Specialties , France

Product Description

Prowaxx 1274 SW is a low-range melting slack wax [SW] in the Prowaxx line of ExxonMobil waxes. It is a translucent crystalline material in the solid state and a water white-to-straw yellow, clear liquid when molten. It is derived from petroleum via a carefully controlled refining process and is primarily comprised of a mixture of straight chain normal paraffin and branched, iso-paraffin hydrocarbons.

This product is produced and controlled according to the ExxonMobil Product Quality Management System, EN ISO 9000 or equivalent standard.

Applications

Prowaxx 1274 SW can be used in the following applications subject to applicable laws and regulations in each jurisdiction*:

- Candles and candle blends
- Wax emulsions and blends
- Wood and fibre board sizing

*User must check compliance with applicable regulations.

Properties and Specifications

Property	Standard Method(a)	Min	Max
ASTM Color by Auto Tristimulus	ASTM D6045		1.0
Kinematic Viscosity @ 100 C, mm ² /s	ASTM D445	2.7	4.1
Oil Content, wt%	ASTM D721		6.0
Melting Point, °C	ASTM D87	50.0	56.0
Flash Point, Cleveland Open Cup, °C	ASTM D92	200	

Note 1: Products are certified on release to meet the values specified. Actual values may deviate within the established reproducibility of the test method specified.

Note 2: For purpose of determining conformance with specification, observed or calculated values shall be rounded off to the nearest unit in the last significant digit used in expressing the limiting value in accordance to the ASTM E 29 method

(a) In lieu of standard test method, alternate test methods may be used for the certification of a product property.

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

02-2024

Esso Société Anonyme Française
20 rue Paul Hérault
92023 NANTERRE CEDEX, France

Tel. +33 (0)1 49 67 90 00

Compte tenu de la continuité dans la recherche et le développement des produits, les informations de cette fiche descriptive sont données à titre indicatif et n'engagent en aucun cas le fabricant. Certains produits peuvent ne pas être disponibles localement.

ExxonMobil

Exxon

Mobil

Esso

XTO
ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved