

**Prowaxx™ 1385 SW**

ExxonMobil Specialties , Portugal

Product Description

Prowaxx™ 1385 SW is a mid-range melting slack wax [SW] in the Prowaxx line of ExxonMobil waxes. It is a translucent crystalline material in the solid state and a yellow-to-dark amber, clear liquid when molten. It is derived from petroleum via a carefully controlled refining process and is primarily comprised of a mixture of straight chain normal paraffin and branched, iso-paraffin hydrocarbons.

This product is produced and controlled according to the ExxonMobil Product Quality Management System, EN ISO 9000 or equivalent standard.

Applications

Prowaxx 1385 SW can be used in the following applications subject to applicable laws and regulations in each jurisdiction* :

- Candles and candle blends
- Wax emulsions and blends
- Wood and fibre board sizing

*User must check compliance with applicable regulations.

Properties and Specifications

Property	Standard Method(a)	Min	Max
Congealing Point, °C	ASTM D938	56.0	62.0
Oil Content, wt%	ASTM D721		15.0
Kinematic Viscosity @ 100 C, mm ² /s	ASTM D445	5.5	7.5
Flash Point, Cleveland Open Cup, °C	ASTM D92	220	
ASTM Color by Auto Tristimulus	ASTM D6045		2.0

Note 1: Products are certified on release to meet the values specified. Actual values may deviate within the established reproducibility of the test method specified.

Note 2: For purpose of determining conformance with specification, observed or calculated values shall be rounded off to the nearest unit in the last significant digit used in expressing the limiting value in accordance to the ASTM E 29 method

(a) In lieu of standard test method, alternate test methods may be used for the certification of a product property.

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

02-2024

ExxonMobil Lubricants & Specialties Europe

Hermeslaan 2

1831 Machelen

BELGIUM

+32-2-722-2111

<http://www.exxonmobil.com>

Every care has been taken in the preparation of this information. To the extent permitted by applicable law, all warranties and/or representations, express or implied, as to the accuracy of the information are disclaimed, and no liability is accepted for the accuracy or completeness of the same.

ExxonMobil

Exxon

Mobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved