



EHC™ 20L

ExxonMobil Basestocks , Japan

製品の概要

ExxonMobilのEHC™基油は、幅広い最終潤滑剤用途で性能を発揮できるよう設計されています。EHC™ 20Lは、自動車のドライブライン、油圧、および熱管理用途で使用されるものなど、さまざまな低粘度潤滑剤に適した超軽量ニュートラル潤滑油用基油です。EHC™ 20Lを使用すると、グループIIIのコンポーネントを削減しながら、性能目標を達成できます。ExxonMobilは、厳格なプロセスに従って一貫した品質の基油を確実に提供することで、お客様が基油の供給に自信を持てるようにします。

特長と利益

EHC 20Lは、お客様が高性能潤滑剤を製造できる品質を提供します。主な機能は次のとおりです。

- ・優れた低温特性と流動点
- ・優れた酸化および熱安定性のための低芳香族
- ・調合者が業界/OEMの要件以上を満たすことを可能にする製品規格
- ・明色

規格

特性	制限	標準法(a)	
セーボルトカラー	最小	ASTM D156	10
粘度指数	最小	ASTM D2270	85
動粘度@100℃、mm2/s	最小～最大	ASTM D445	2.1-2.6
引火点、クリーブランド開放式試験、℃	最小	ASTM D92	150
流動点、℃	最大	ASTM D97	-30
外観	最小～最大	視覚的	クリアで鮮明
動粘度@40℃、mm2/s	最小	ASTM D445	7

注1: 製品はリリース時に、指定された値を満たしていることが認定されています。実際の値は、指定された試験方法の確立された再現性の範囲内で逸脱する場合があります。

注2: 仕様に対する適合性を判断する目的で、観測値または計算値は、ASTM E 29方法に従って制限値を表す際に使用される最後の有効数字の最も近い単位に丸められるものとします。

(a) 標準試験方法の代わりに、代替試験方法を使用して製品特性を証明することができます。

健康と安全

本製品の健康と安全に関する情報については、<https://sds.exxonmobil.com/>にある安全データシート(SDS)をご覧ください。
特に明記されていない限り、ここで使用されている商標は全て、Exxon Mobil Corporationまたは同社の子会社の商標または登録商標です。

3225 Gallows Road
Fairfax, VA 22037-001

1-800-662-4592
<http://www.exxonmobil.com>

All products may not be available in all countries. Every care has been taken in the preparation of this information. Typical values may vary within modest ranges and specifications may be subject to change. To the extent permitted by applicable law, all warranties and/or representations, express or implied, as to the accuracy of the information are disclaimed, and no liability is accepted for the accuracy or completeness of the same.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names which include Esso, Mobil, Exxon, or ExxonMobil. For convenience and simplicity, the term ExxonMobil may be used to represent all of these entities, and the products and services provided by those entities. Nothing in this brochure is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with local ExxonMobil-affiliated entities.

The ExxonMobil logo, featuring the word "Exxon" in a bold, sans-serif font and "Mobil" in a slightly lighter, sans-serif font, both in white against a dark background.

© Copyright 2003-2024 Exxon Mobil Corporation. All
Rights Reserved