

Mobil 2 Stroke Oil

Mobil Passenger Vehicle Lube , Australia

Superior Performance Two-Stroke Engine Oil

Product Description

Mobil 2 Stroke Oil is a low ash high performance lubricant designed for 2 stroke petrol fuelled engines. It is recommended for land based air cooled 2 stroke engines such as lawnmowers, weed eaters, chainsaws, motorcycles and auxiliary equipment.

Mobil 2 Stroke Oil is pre-diluted to facilitate mixing when added to fuel, and is ideal for direct injection and pre-mix engines.

Features and Benefits

Mobil 2 Stroke Oil combines a blend of high quality mineral and synthesised high performance baseoils with an advanced additive system to provide excellent engine cleanliness and no-smoke exhaust performance. Key features and benefits include:

Features	Advantages and Potential Benefits
Excellent wear protection	Longer engine life
Good thermal and oxidation stability and deposit control	Cleaner engines resulting in extended spark plug and valve life, reduced ring sticking, piston tightening and prevention of pre-ignition problems
Excellent corrosion protection properties	Longer engine life
Smoke-free exhaust	Cleaner environment

Specifications and Approvals

Mobil 2 Stroke Oil meets or exceeds the requirements of the following industry specifications:	
API	TC
ISO	L-EGD
JASO	FD

Typical Properties

Mobil 2 Stroke Oil	
Viscosity, cSt ASTM D 445	
cSt @ 40° C	48
cSt @ 100° C	7.9
Viscosity Index, ASTM D 2270	134
Sulfated Ash, wt%, ASTM D 874	0.09
Pour Point, °C, ASTM D 97	-12
Flash Point, °C, ASTM D 93	96
Density @15° C kg/l, ASTM D 4052	0.866

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the

recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2019

Mobil Oil Australia Pty Ltd

A.B.N. 88 004 052 984

12 Riverside Quay

Southbank Vic 3006

+61 3 8633 8444

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil Esso XTO ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved