Mobil Special™ 20W-50 Page 1 of 2



Mobil Special™ 20W-50

Mobil Passenger Vehicle Lube, Australia

High Performance Motor Oil

Product Description

Mobil Special™ 20W-50 is a high performance motor oil for all types of vehicles. Mobil Special 20W-50 delivers engine protection and cleanliness. Mobil Special 20W-50 is recommended for use in a wide range of applications and operating conditions.

Features and Benefits

- Helps reduce engine wear and corrosion
- Helps keep engine clean
- Multigrade motor oil allowing easier starts at low temperatures
- Good high temperature properties

Specifications and Approvals

This product is recommended for use in applications requiring:	
API CF	

This product meets or exceeds the requirements of:

API SJ

Properties and Specifications

Property	
Grade	SAE 20W-50
Mini-Rotary Viscometer, Apparent Viscosity, -20 C, mPa.s, ASTM D4684	23300
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	18.7
Pour Point, °C, ASTM D97	-24
Viscosity Index, ASTM D2270	126
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	166
Hi-Temp Hi-Shear Viscosity @ 150 C, mPa.s, ASTM D4683	4.9
Flash Point, Cleveland Open Cup, °C, ASTM D92	266
Ash, Sulfated, mass%, ASTM D874	0.9
Total Base Number, mgKOH/g, ASTM D2896	8.1

Mobil Special™ 20W-50 Page 2 of 2

Property	
Density @ 15.6 C, g/ml, ASTM D4052	0.888

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims/psims.aspx

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2022 Mobil Oil Australia Pty Ltd A.B.N. 88 004 052 984 12 Riverside Quay Southbank Vic 3006 +61 3 8633 8444

http://www.exxonmobil.com

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

