



Mobilfluid™ 428 V2

Mobil Commercial Vehicle Lube , Bolivia

Modern extra high performance multipurpose tractor oil (UTTO)

Product Description

Mobilfluid 428 V2 is a modern extra high performance multipurpose tractor lubricant engineered to meet or exceed the requirements of most equipment builders for hydraulic and transmission compartments. It is designed to optimize the performance of agricultural and commercial tractors operating in a wide range of environments and conditions. Mobilfluid 428 V2 is recommended to be used in off-highway industries including: agriculture, construction, and quarrying. Its friction characteristics helps reduce wet brake and Power Take-Off (PTO) chatter. This next generation product is formulated from high quality base oils and advanced additive technology to deliver excellent thermal stability combined with high shear stability for an SAE 10W-30 viscosity grade. Based on the excellent shear stability and air handling, Mobilfluid 428 V2 is suitable for use in conventional CVTs (hydraulic pump plus planetary gear componentry).

Features and Benefits

Next generation technology has vastly improved the performance capabilities of heavy-duty equipment in terms of load, speed, control, and reliability through innovative powertrain designs. These designs have changed and increased the requirements of powertrain fluids to deliver higher levels of performance and productivity while reducing operating costs. Friction control, wear protection, thermal stability, shear stability, rust and corrosion protection, and pumpability are features that must be optimally balanced to provide extended clutch life, maximum drawbar loading, and maintain operations on uneven terrain over a wide range of ambient temperatures. Mobilfluid 428 V2 delivers exceptional performance in today's powertrain transmissions, drive axles, clutches, PTOs and hydraulic systems.

The key benefits include:

Features	Advantages and Potential Benefits
Excellent frictional properties Improved wet brake and PTO chatter control	Optimal clutch and PTO performance
Compatible with clutch materials and elastomers	Long clutch life and reduced leakage
High viscosity index and improved shear stability	Consistent operating response
Excellent protection against rust, corrosion, and yellow metal etching	Protects equipment in wet or humid environments and prevents premature wear
Enhanced low temperature properties	Responsive operation and effective lubrication in cold weather applications
Strong anti-wear and extreme pressure properties	Reduces wear, extends equipment life, and reduces maintenance costs
Excellent thermal and oxidation stability	Reduces deposits, extends seal life, and increases service life of equipment and lubricant
Multipurpose capability	Simplifies inventory and reduces misapplication problems
Good filterability	Keeps systems clean and operating smoothly

Specifications and Approvals

This product has the following builder approvals:

VOLVO WB-101

This product is recommended for use in applications requiring:

AGCO Powerfluid 821 XL

Allison C-4

API GL-4

Caterpillar TO-2

CNH MAT 3505

CNH MAT 3525

CNH MAT 3540

Denison UTTO/THF

Ford ESEN-M2C86-B

FORD ESN-M2C134-D

FORDNH FNHA-2-C-201.00

G2-08

GEAR OIL HP

JICASE MS 1204

JICASE MS 1205

JICASE MS 1206

JICASE MS 1207

JICASE MS 1209

KUBOTA UDT

MASSEY FERGUSON CMS M1135

MASSEY FERGUSON CMS M1141

MASSEY FERGUSON CMS M1143

New Holland WB NWH 410B

RENAULT AGRICULTURE (M1145)

This product meets or exceeds the requirements of:

This product meets or exceeds the requirements of:

ASTM D6973 (Eaton 35VQ) vane pump test

JOHN DEERE JDM J20C

Properties and Specifications

Property	
Grade	SAE 10W-30
Flash Point, Cleveland Open Cup, °C, ASTM D92	237
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	60.5
Density @ 15 C, g/ml, ASTM D4052	0.8681
Viscosity Index, ASTM D2270	139
Pour Point, °C, ASTM D97	-42

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2024




© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved