



Mobil Delvac™ Modern 15W-40 Light Commercial

Mobil Commercial Vehicle Lube , Brazil

Mobil commercial-vehicle-lube

Product Description

Mobil Delvac™ Modern 15W-40 Light Commercial is an engine oil that provides excellent lubrication of diesel and gasoline engines operating in severe driving conditions typically encountered in city operations. This product is recommended by ExxonMobil for European, Russian and American engines for use in a wide range of traditional light-duty commercial vehicles.

Features and Benefits

Mobil Delvac™ Modern 15W-40 Light Commercial is formulated from high performance base oils and a superior balanced additive system to provide optimum engine performance in modern diesel and gasoline engines as well as older models. Key benefits include:

| Features | Advantages and Potential Benefits |
|--|---|
| Increased thermal and oxidation stability | Help to reduced sludge build-up, deposits, and long oil and engine life |
| Enhanced wear protection | Helps towards long component and engine life |
| Improved corrosion protection | Helps to reduce bearing wear to assist with long drain intervals in modern diesel engines |
| Advanced piston deposit control | Helps to keep engines clean with reduced maintenance costs and long engine life |
| Advanced soot handling to control viscosity increase, sludge build up, and filter pressure | Helps to enhance engine protection for long engine life |
| Enhanced low temperature pumpability | Fast start up with reduced wear operating in low temperature climates |

Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered engines built by European, Russian, and American manufacturers.
- On-highway light trucking including mixed fleets with gasoline engines.
- For GAZ Light Duty Vehicles with diesel or petrol engines requiring API CI-4 or API SL motor oils.

Specifications and Approvals

| This product has the following approvals: |
|---|
| MB 228.3 |
| Cummins CES 20076 |
| Cummins CES 20077 |
| Cummins CES 20078 |

This product is recommended for use in applications requiring:

ACEA A2-96 Issue 3

ACEA B2-98 Issue 2

API CF

This product meets or exceeds the requirements of:

API CH-4

API CI-4

API SJ

API SL

ACEA E7-16

Caterpillar ECF-2

JASO DH-1

Properties and Specifications

| Property | |
|--|------------------|
| Grade | SAE 15W-40 |
| Density @ 15.6 C, kg/l, ASTM D4052 | 0.88 |
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 14.4 |
| Ash, Sulfated, mass%, ASTM D874 | 1.3 |
| Flash Point, °C, ASTM D92 | 228 |
| Pour Point, °C, ASTM D97 | -30 |
| Viscosity Index, ASTM D2270 | 140 |
| Total Base Number, mgKOH/g, ASTM D2896 | 11.9 |
| Noack Volatility, mass%, ASTM D5800 | 11.6 |
| Appearance, AMS 1738 | Clear and Bright |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2024

Cosan Lubrificantes e Especialidades S.A.

Praia da Ribeira, 01

21930-080 Rio de Janeiro – RJ - BRASIL

Tel: 0800 644 1562

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved