Mobil™ Hidraulico 68 Page 1 of 2

Mobil™ Hidraulico 68

Mobil Industrial, Brazil

Hydraulic Oil

Product Description

Mobil Hidráulico 68 is a good hydraulic oil formulated to deliver good performance in a range of hydraulic components on industrial and mobile service applications, subjected to moderate operating conditions.

Applications

Industrial and mobile service applications, subjected to moderate operating conditions.

Properties and Specifications

Property	
Grade	ISO 68
Pour Point, °C, ASTM D97	-3
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	8.1
Viscosity Index, ASTM D2270	90
Specific Gravity, 20 C/4 C, ASTM D1298	0.8774
ASTM Color, ASTM D1500	4
Rust Characteristics, Procedure B, ASTM D665	Pass
Flash Point, Cleveland Open Cup, °C, ASTM D92	204
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	68.3

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims/psims.aspx

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

03-2023

Cosan Lubrificantes e Especialidades S.A.

Praia da Ribeira, 01

21930-080 Rio de Janeiro - RJ - BRASIL

Tel: 0800 644 1562

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Mobil™ Hidraulico 68 Page 2 of 2

