



Mobil 1™ Truck & SUV

Mobil Passenger Vehicle Lube , Canada

Advanced Full Synthetic Motor Oil

Product Description

Mobil 1™ Truck & SUV oils are advanced full synthetic motor oils formulated specifically for hardworking truck and SUV gasoline powered engines. These oils help protect critical engine parts for up to 16,000 kilometers between oil changes*. Mobil 1 Truck & SUV oils meet or exceed the industry's toughest standards and protect in tough conditions like towing and hauling. Mobil 1™ synthetic motor oil technology comes as standard equipment in many different vehicles, including select high-performance vehicles.

Features and Benefits

Mobil 1™ Truck & SUV motor oils are designed and formulated for hardworking truck & SUV engines and are made with a proprietary blend of high performance synthetic base stocks fortified with a precisely balanced additive component system. Mobil 1 Truck & SUV motor oils are designed to provide outstanding overall engine protection, while meeting or exceeding the latest industry performance standards.

Key features and potential benefits include:

Features	Advantages and Potential Benefits
Advanced full synthetic formula	Designed to help maximize engine performance and protection
Outstanding thermal and oxidation stability	Protects for up to 16,000 kilometers between oil changes*

Applications

Mobil 1™ Truck & SUV motor oils are designed for gasoline-powered trucks and SUVs and are recommended for all types of modern gasoline-powered vehicles, including high-performance turbocharged, supercharged, multi-valve fuel injected engines found in passenger cars, SUVs, light vans and light trucks.

- Mobil 1 Truck & SUV is not recommended for 2-Cycle or aviation engines, unless specifically approved by the manufacturer.

Always check your owner's manual for the manufacturer's recommended oil viscosity grade, API service classification and any builder approval.

*Protection for up to 16,000 kilometers or 1 year, whichever comes first. To learn more about the Mobil 1 Limited Warranty, visit mobil1.ca.

Specifications and Approvals

This product has the following approvals:	MOBIL 1 TRUCK & SUV 0W-20	MOBIL 1 TRUCK & SUV 5W-20	MOBIL 1 TRUCK & SUV 5W-30
GM dexos1:GEN3 Licensed	X		X

This product is recommended for use in applications requiring:			
FORD WSS-M2C945-A		X	

This product is recommended for use in applications requiring:			
FORD WSS-M2C946-B1			X
GM 6094M	X	X	

This product meets or exceeds the requirements of:			
API SJ	X	X	X
API SL	X	X	X
API SM	X	X	X
API SN	X	X	X
API SN PLUS	X	X	X
API SN PLUS RESOURCE CONSERVING	X	X	X
API SN Resource Conserving	X	X	X
API SP	X	X	X
API SP Resource Conserving	X	X	X
ILSAC GF-6A	X	X	X
CHRYSLER MS-13340			X
CHRYSLER MS-6395	X	X	X
FORD WSS-M2C960-A1		X	
FORD WSS-M2C961-A1			X
FORD WSS-M2C962-A1	X		
FORD WSS-M2C945-B1		X	
Ford WSS-M2C946-A			X
Ford WSS-M2C947-A	X		
Ford WSS-M2C947-B1	X		

Properties and Specifications

Property	MOBIL 1 TRUCK & SUV 0W-20	MOBIL 1 TRUCK & SUV 5W-20	MOBIL 1 TRUCK & SUV 5W-30
Grade	SAE 0W-20	SAE 5W-20	SAE 5W-30
Density @ 15.6 C, g/ml, ASTM D4052	0.8467	0.8419	0.8513
Flash Point, Cleveland Open Cup, °C, ASTM D92	235	235	261

Property	MOBIL 1 TRUCK & SUV 0W-20	MOBIL 1 TRUCK & SUV 5W-20	MOBIL 1 TRUCK & SUV 5W-30
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	8.2	8.3	10
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	42	46	57
Pour Point, °C, ASTM D97	-39	-36	-42

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

10-2022

Imperial Oil

Petroleum and Chemicals Division

Lubricants and Specialties

240 Fourth Ave SW

C. P. 2480, Station M

Calgary AB T2P 3 M 9

1-800-268-3183

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved