



Mobil 1™ X2 5W-30

Mobil Passenger Vehicle Lube , 中国

Advanced Full Synthetic Engine Oil

Product Description

Mobil 1™ X2 5W-30 is an advanced full synthetic engine oil designed for delivering great engine performance. Mobil 1™ X2 5W-30 helps to provide cleanliness, wear protection and fuel economy to gasoline engines. Mobil 1™ X2 5W-30 keeps your engine running like new* in all driving conditions.

* Based on the MADS test result in US in 2021.

Features and Benefits

- Excellent engine performance and wear protection.
- Enhanced frictional properties, excellent fuel economy.
- Quick cold weather starting for ultra-fast protection.
- Keeps your engine clean.
- Protects engines working under high temperatures.
- Provide excellent LSPI protection.

Applications

Mobil 1™ X2 5W-30 is recommended for many types of modern vehicles where it will help provide the performance required even under demanding driving conditions.

Mobil 1™ X2 5W-30 is not recommended for 2-Cycle or aviation engines, unless specifically approved by the manufacturer.

* Always check your owner's manual for the manufacturer's recommended oil viscosity grade, API service classification and any builder approval.

** General Motors (GM) Dexos1™ Gen3 is obtainable for Mobil 1™ X2 5W-30.

Specifications and Approvals

This product is recommended for use in applications requiring:
FIAT 9.55535-CR1
FORD WSS-M2C929-A
FORD WSS-M2C946-A
Ford WSS-M2C946-B1
GM 6094M

This product meets or exceeds the requirements of:

API SP

ACEA C2

ACEA A5/B5-21

ILSAC GF-6A

CHRYSLER MS-13340

CHRYSLER MS-6395

FORD WSS-M2C961-A1

Properties and Specifications

Property	
Grade	SAE 5W-30
Pour Point, °C, ASTM D97	-39
Flash Point, Cleveland Open Cup, °C, ASTM D92	235
Density @ 15.6 C, g/ml, ASTM D4052	0.852
Viscosity Index, ASTM D2270	157
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	10.3
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	61
Ash, Sulfated, mass%, ASTM D874	0.76
Total Base Number, mgKOH/g, ASTM D2896	9.2
Mini-Rotary Viscometer, Apparent Viscosity, -35 C, mPa.s, ASTM D4684	13700

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

01-2024

ExxonMobil (China) Investment Co. Ltd

17th Floor, Metro Tower

30 Tian Yao Qiao Road

Shanghai 2000030

China

+86 21 24076000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil Esso XTO
ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved