



Mobil Super™ 3000 Formula M 5W-40

Mobil Passenger Vehicle Lube , Colombia

Full Synthetic Engine Oil

Product Description

Mobil Super™ 3000 Formula M 5W-40 is a fully synthetic, high performance motor oil primarily intended for use in Mercedes Benz (MB) vehicles where a product for extended service intervals (Long Life) service intervals is required

Features and Benefits

Mobil Super 3000 Formula M 5W-40 provides the following features and benefits:

- Permits extended operation at elevated temperatures without oxidative oil thickening and oil breakdown.
- Provides excellent fluidity at low temperatures allowing easy winter starting and rapid oil circulation around the engine.
- Suitable for use in both gasoline and some diesel engine passenger car and light commercial vehicles.

Applications

Mobil Super 3000 Formula M 5W-40 has been developed to meet the highest specifications for motor oils required by Mercedes Benz. It offers excellent performance at both very low and very high operating temperatures and long term engine protection from wear and sludge.

Specifications and Approvals

This product meets or exceeds the requirements of:
API SN
ACEA A3/B4

Properties and Specifications

Property	
Grade	SAE 5W-40
Pour Point, °C, ASTM D97	-36
Viscosity Index, ASTM D2270	169
Hi-Temp Hi-Shear Viscosity @ 150 C, mPa.s, ASTM D4683	3.8
Density @ 15 C, kg/l, ASTM D1298	0.85
Total Base Number, mgKOH/g, ASTM D2896	10

Property	
Ash, Sulfated, mass%, ASTM D874	1.07
Flash Point, Cleveland Open Cup, °C, ASTM D92	232
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	83
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	13.7

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2024

Organización Terpel S.A.

Address: Carrera 7 N° 75-51, Bogotá – Colombia

Phone: (57) 1 3267878

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved