



MOBIL DELVAC MODERN 5W30 ADVANCED PROTECTION V3

Mobil Commercial Vehicle Lube , Germany

Advanced high Performance diesel engine oil

Product Description

Mobil Delvac Modern 5W-30 Advanced Protection V3 is an Advanced high performance diesel engine oil engineered to provide outstanding protection and fuel economy potential in modern, high performance, low emissions engines used in severe on-highway applications. It is formulated with advanced synthetic technology base oils and additive system which provide excellent low temperature fluidity, high temperature viscosity retention, volatility control and contribute to fuel economy improvement potential while prolonging the life and maintaining the efficiency of emission reduction systems such as the Diesel Particulate Filter (DPF).

Mobil Delvac Modern 5W-30 Advanced Protection V3 is also biodiesel compatible.\*

\*Follow OEM recommendations on potential service adjustments

Features and Benefits

High output, low emission diesel engines significantly increase demands on engine lubricants. Tighter engine design, use of inter-coolers, and turbochargers increase mechanical and thermal stresses on the lubricant. Low emission engine technologies such as higher fuel injection pressure, retarded timing and after-treatment devices all require improved oil performance in areas such as oxidation stability, soot dispersancy, volatility and compatibility with after-treatment devices. The advanced technology in Mobil Delvac Modern 5W-30 Advanced Protection V3 delivers exceptional performance and protection of exhaust systems fitted with Diesel Particulate Filters. The key benefits include:

| Features                                                                                                     | Advantages and Potential Benefits                                                                                                                                                                                                                                                                                             |
|--------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Excellent protection against oil thickening, oil degradation, high temperature deposits, and sludge build-up | Contributes to long oil life consistent with OEM recommended Oil Drain Intervals (ODI)<br>Helps prevent ring sticking for better engine protection and efficiency                                                                                                                                                             |
| Excellent protection against wear, scuffing, bore polishing, and corrosion                                   | Helps control wear in heavy duty operation, promoting long engine life                                                                                                                                                                                                                                                        |
| Excellent low temperature fluidity                                                                           | Contributes to excellent oil pumpability and circulation allowing operation in cold climate regions<br>Helps protect against wear during cold engine start-up                                                                                                                                                                 |
| Advanced "Low Ash" componentry                                                                               | Helps improve efficiency and extend durability of emission exhaust systems fitted with Diesel Particulate Filters (DPF)                                                                                                                                                                                                       |
| Advanced formulation viscometrics<br>. SAE 5W-30<br>. Stay-in-grade shear stability<br>. Very low volatility | Potentially helps to reduce fuel consumption over higher viscosity grade engine oils without compromising engine durability (potential fuel economy depending on vehicle type and driving conditions)<br><br>Helps to control viscosity breakdown and oil consumption under heavy duty, high temperature operating conditions |

Specifications and Approvals

This product has the following approvals:

**This product has the following approvals:**

DTFR 15C110

**This product is recommended for use in applications requiring:**

ACEA E6

ACEA E9

**This product meets or exceeds the requirements of:**

API CK-4

DAF Extended Drain

**Properties and Specifications**

| Property                                                   |           |
|------------------------------------------------------------|-----------|
| Grade                                                      | SAE 5W-30 |
| Density @ 15 C, g/ml, ASTM D4052                           | 0.8408    |
| Pour Point, °C, ASTM D97                                   | -39       |
| Flash Point, Cleveland Open Cup, °C, ASTM D92              | 233       |
| Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445  | 72.0      |
| Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445 | 12.0      |
| Viscosity Index, ASTM D2270                                | 164       |
| Ash, Sulfated, mass%, ASTM D874                            | 0.95      |
| Total Base Number, mgKOH/g, ASTM D2896                     | 9.8       |

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2024

EXXONMOBIL LUBRICANTS &amp; SPECIALTIES EUROPE, A DIVISION OF EXXONMOBIL PETROLEUM &amp; CHEMICAL, BVBA (EMPC)

POLDERDIJKWEG

B-2030 Antwerpen

Belgium

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobil.com/de/de-de/kontakt>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit

[www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

