



Mobil 1™ ESP 5W-30

Mobil Passenger Vehicle Lube , France

Advanced Full Synthetic Engine Oil

Product Description

Mobil 1™ ESP 5W-30 advanced performance synthetic engine oil is a select member of Mobil 1™, the world's leading synthetic engine oil brand delivering our ultimate performance and protection. Mobil 1™ ESP 5W-30 is engineered to deliver excellent all-round protection for Euro 6 and prior gasoline and diesel powered automobiles, and meets or exceeds the requirements of many leading car manufacturers.

Mobil 1 keeps your engine running like new!

Features and Benefits

Mobil 1 ESP 5W-30 is made with a proprietary blend of leading edge components formulated to help provide exceptional cleaning power and wear protection, and be fully compatible with the Diesel Particulate Filters (DPF's) and Gasoline Catalytic Converters (CAT's).

| Features | Advantages and Potential Benefits |
|--|--|
| Low Ash content | Helps to reduce particulate build-up in Diesel Particulate Filters |
| Low Sulphur and Phosphorous content | Helps to reduce poisoning of Gasoline Catalytic Converters |
| Active cleaning agents | Helps to reduce deposits and sludge build-up to enable clean and long engine life |
| Excellent thermal and oxidative stability | Helps to reduce oil aging allowing extended drain interval protection |
| Excellent low temperature capabilities | Quick cold weather starting and fast protection to help extend engine life |
| Meets industry latest LSPI requirements for gasoline direct injection turbocharged engines | Helps prevent engine breakdown resulting from pre-ignition occurrences at engine low speed and high torque operation |

Applications

Mobil 1 ESP 5W-30 carries recommendations for a wide range of passenger cars, SUVs and light vans. It is designed for modern high efficiency gasoline, diesel and hybrid cars from Porsche, BMW, Volkswagen, Opel and Mercedes-Benz as well as for Japanese and Korean vehicles that specifically call for a SAE 5W-30 viscosity grade and any of the specifications the oil supports, allowing for extended oil change intervals where recommended by the manufacturer.

- Mobil 1 ESP 5W-30 is a low ash (mid SAPS) engine oil to help protect exhaust gas after-treatment systems designed to limit engine emissions. It fully meets or exceeds ACEA C3 industry standard and is suitable for the operation and protection of engines and after-treatment systems of vehicles calling for ACEA C2. However it only provides the fuel economy potential required by the C3 and not the C2 classification.
- Mobil 1 ESP 5W-30 meets or exceeds the requirements of 'API SP' industry standard therefore helping address LSPI (Low Speed Pre-Ignition) and making it a preferred choice for modern downsized direct injection turbocharged gasoline engines.
- Mobil 1 ESP 5W-30 is especially suitable for extreme conditions where conventional oil often may not perform.
- Mobil 1 ESP 5W-30 is not recommended for 2-Cycle or aviation engines, unless specifically approved by the manufacturer.

Owner's manual should be consulted for recommended viscosity grade and specification.

Specifications and Approvals

| This product has the following approvals: | |
|--|--|
| BMW Longlife 04 | |
| MB-Approval 229.31 | |
| MB-Approval 229.51 | |
| MB-Approval 229.52 | |
| OV 040 1547 – D30 | |
| OV 040 1547 – G30 | |
| Porsche C30 | |
| VW 504 00 | |
| VW 507 00 | |

| This product is recommended for use in applications requiring: | |
|---|--|
| FIAT 9.55535-S3 | |
| Recommended by ExxonMobil for applications requiring ACEA C2 | |

| This product meets or exceeds the requirements of: | |
|---|--|
| API SJ | |
| API SL | |
| API SM | |
| API SN | |
| API SN PLUS | |
| API SP | |
| ACEA C3 | |

Properties and Specifications

| Property | |
|----------|-----------|
| Grade | SAE 5W-30 |

| Property | |
|---|-------|
| Pour Point, °C, ASTM D97 | -42 |
| Ash, Sulfated, mass%, ASTM D874 | 0.8 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 234 |
| Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445 | 67 |
| Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683 | 3.5 |
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 11.9 |
| Density @ 15.6 C, g/ml, ASTM D4052 | 0.851 |
| Viscosity Index, ASTM D2270 | 175 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2024

Esso Société Anonyme Française

20 rue Paul Héroult
92000 Nanterre, France

Société Anonyme au capital de 98 337 521,70 euros

RCS Nanterre 542 010 053

You can always contact our Technical Help Desk engineers on Mobil lubricants and services related questions: <https://www.mobil.fr/fr-fr/contact-us>

Tel. +33 (0)1 49 67 90 00

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved