



Mobil Delvac Legend 15W-40 Standard Defense

Mobil Commercial Vehicle Lube , Indonesia

Heavy Duty Engine Oil

Product Description

Mobil Delvac Legend 15W-40 Standard Defense is high performance, heavy duty engine oil that provides complete protection to diesel engines operating in severe on and off-highway service applications. Mobil Delvac Legend 15W-40 Standard Defense is recommended for use in a wide range of heavy duty applications and operating environments found in the trucking, construction and agricultural industries.

Features and Benefits

The key benefits of Mobil Delvac Legend 15W-40 Standard Defense:

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Controls sludge build-up and deposits
Excellent detergency/dispersancy	Cleaner engines and longer engine life
Stay-in-grade shear stability	Helps reduce oil consumption and wear

Applications

Recommended by ExxonMobil for use in:

- Diesel-powered equipment from leading diesel engine manufacturers
- On-highway light and heavy duty trucking
- Off-highway industries including: trucking, construction, quarrying, and agriculture
- Mixed diesel/gasoline engine fleets

Specifications and Approvals

This product is recommended for use in applications requiring:
API CF-4

Properties and Specifications

Property	
Grade	SAE 15W-40
Density @ 15 C, g/ml, ASTM D1298	0.87
Total Base Number, mgKOH/g, ASTM D2896	9

Property	
Pour Point, °C, ASTM D97	-30
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	114.2
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	14.9
Flash Point, Cleveland Open Cup, °C, ASTM D92	236

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2023

ExxonMobil Asia Pacific Pte Ltd
Jakarta Representative Office
Wisma GKBI 27th Floor
Jl. Jenderal Sudirman No. 28
Jakarta 10210
Indonesia

+62 21 574 0707

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved