



Mobil Extra 2T

Mobil Passenger Vehicle Lube , India

Superior Performance Two-Stroke Engine Oil

Product Description

Mobil Extra 2T is a high performance; semi-synthetic, smokeless, two-stroke engine oil developed to meet for high performance motorcycles, snowmobiles and chain saws.

Mobil Extra 2T is pre-diluted to facilitate mixing when added to fuel.

Features and Benefits

Mobil Extra 2T combines a blend of high quality mineral and synthesised high performance baseoils with an advanced additive system to provide excellent engine cleanliness and no-smoke exhaust performance. Key features and benefits include:

| Features | Advantages and Potential Benefits |
|--|---|
| Excellent wear protection | Longer engine life |
| Good thermal and oxidation stability and deposit control | Cleaner engines resulting in extended spark plug and valve life, reduced ring sticking, piston tightening and prevention of pre-ignition problems |
| Excellent corrosion protection properties | Longer engine life |
| Smoke-free exhaust | Cleaner environment |

Specifications and Approvals

| Mobil Extra 2T meets or exceeds the requirements of the following industry specifications: | |
|--|-------|
| API | TC |
| ISO | E-GC |
| JASO | FC/FD |

Properties and Specifications

| Property | |
|--|------|
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 8.8 |
| Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445 | 55 |
| Viscosity Index, ASTM D2270 | 135 |
| Ash, Sulfated, mass%, ASTM D874 | 0.06 |
| Pour Point, °C, ASTM D97 | -24 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 110 |

| Property | |
|----------------------------------|--------|
| Density @ 15 C, g/ml, ASTM D4052 | 0.8670 |

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2021

ExxonMobil Services & Technology Private Limited
(CIN: U74900KA2015FTC080245)

Tower A, 5th Floor, Crescent #1, Prestige Shantiniketan Building,
Whitefield Main Road, Bangalore – 560048, Karnataka, India


+918071085300

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003–2024 Exxon Mobil Corporation. All Rights Reserved