



Mobil Super Diesel 10W-30

Mobil Passenger Vehicle Lube , South Korea

Extra Performance Diesel Motor Oil

Product Description

Mobil Super Diesel 10W-30 is a premium quality motor oil designed to provide very high level of protection for diesel powered engines on highway passenger diesel SUV and light duty trucks.

Features and Benefits

The key benefits of Mobil Super Diesel 10W-30 includes:

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Controls sludge build-up and deposits
Excellent detergency/dispersancy	Cleaner engines and longer engine life
Stay-in-grade shear stability	Helps reduce oil consumption and wear

Applications

Recommended by ExxonMobil for use in:

- Diesel-powered equipment from leading diesel engine manufacturers
- On highway passenger diesel SUV and light duty trucks

Specifications and Approvals

MobilSuper Diesel 10W-30 recommended by ExxonMobil for use in applications requiring	10W-30
API CF-4/SF/SG	X

Typical Properties

MobilSuperDiesel 10W 30	
SAE Grade	10W-30
Viscosity, ASTM D 445	
cSt @ 100°C	10.7
Sulfated Ash, wt%, ASTM D 874	0.8
Total Base # , mg KOH/g, ASTM D 2896	8.2
Pour Point, °C, ASTM D 97	-39
Flash Point, °C, ASTM D 92	223

MobilSuperDiesel 10W 30	
Density @ 15°C kg/l, ASTM D 4052	0.87

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and Delvac are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

05-2020

Mobil Korea Lube Oil Inc.


Level 22, Seoul Square bd., Hangang-daero, Jung-gu, Seoul, Korea

+82-2-750-8700

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved