



Mobil Delvac Modern™ 10W-30 Super Defense V2

Mobil Commercial Vehicle Lube , Sri Lanka

Synthetic Technology Commercial Vehicle Engine Oil

Product Description

Mobil Delvac Modern™ 10W-30 Super Defense V2 is formulated to deliver high performance in modern multipurpose, high performance diesel and gasoline medium duty commercial vehicle as well as heavy duty commercial vehicle, including turbo-charged and intercooled units.

This product is fully compatible with Mobil Delvac MX 10W-30 and can be used as a replacement of same.

Features and Benefits

High output, low emission diesel engines significantly increase the demands on engine lubricants. Tighter engine designs reduce oil consumption, resulting in less fresh oil make-up to replenish depleted additives. Top piston fire rings are located higher on the piston bringing the oil film closer to the combustion chamber where higher temperatures increase thermal stress on the lubricant. Increased fuel injector pressure and retarded timing improve fuel burn efficiency, but also increase engine temperatures and increase soot loads. Mobil Delvac Modern 10W-30 Super Defense V2 is formulated from high performance base oils and a balanced additive system to provide optimum engine performance in modern diesel and gasoline engines as well as older models. The key benefits include:

Features	Advantages and Potential Benefits
High thermal and oxidation stability	Reduced sludge build-up, deposits and viscosity increase
TBN reserves	Deposit control and acid neutralisation
Stay-in-grade shear stability	Wear protection and viscosity control
High detergency/dispersancy	Clean engines and long component life
Improved soot handling	Improved viscosity control and used oil pumpability
Excellent low temperature properties	Start-up wear protection
Component compatibility	Long gasket and seal life

Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered equipment.
- On-highway medium and heavy duty trucking.
- Off-highway industries including: construction, mining, quarrying, and agriculture.
- Mixed fleet applications.

Specifications and Approvals

This product meets or exceeds the requirements of:

This product meets or exceeds the requirements of:
API CI-4
API SL

Properties and Specifications

Property	
Grade	SAE 10W-30
Ash, Sulfated, mass%, ASTM D874	1.1
Density @ 15 C, kg/l, ASTM D4052	0.867
Viscosity Index, ASTM D2270	141
Total Base Number, mgKOH/g, ASTM D2896	9
Flash Point, Cleveland Open Cup, °C, ASTM D92	225
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	11.7
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	79.5
Pour Point, °C, ASTM D97	-36

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

03-2024

ExxonMobil

Exxon

Mobil

Esso

XTO ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved