



Mobil Delvac XHP™ 15W-40

Mobil Commercial Vehicle Lube , Luxembourg

High Performance Diesel Engine Oil

Product Description

Mobil Delvac XHP™ 15W-40 is a high performance diesel engine oil that provides protection for diesel engines operating under severe service conditions for both on- and off-highway applications. Mobil Delvac XHP 15W-40 is recommended by ExxonMobil for use in a wide range of heavy-duty applications and operating environments found in the trucking, mining, construction, quarrying, and agricultural industries.

Features and Benefits

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Helps to control sludge build-up and deposits
TBN reserve	Helps to control deposits
Stay-in-grade shear stability	Helps to reduce oil consumption and to provide wear protection
Excellent detergency/ dispersancy	Helps to protect and to maintain engines clean
Component compatibility	Long gasket and seal life

Applications

- Naturally aspirated and turbo-charged diesel powered equipment of European, Japanese and American manufacturers in line with owner manual recommendations
- On-highway light and heavy-duty trucking
- Off-highway industries including: construction, mining, quarrying and agriculture

Specifications and Approvals

This product has the following approvals:
MTU Oil Category 1

This product is recommended for use in applications requiring:
ACEA B2
API CF
API CF-4

This product is recommended for use in applications requiring:

API CG-4

API SH

MAN M 3275-1

RENAULT TRUCKS RD

RENAULT TRUCKS RD-2

RENAULT TRUCKS RLD

VOLVO VDS-2

This product meets or exceeds the requirements of:

API CH-4

API SJ

Properties and Specifications

Property	
Grade	SAE 15W-40
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	110
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	14.6
Density @ 15 C, lb/USg, ASTM D4052	0.87
Total Base Number, mgKOH/g, ASTM D2896	9.2
Viscosity Index, ASTM D2270	136
Ash, Sulfated, mass%, ASTM D874	1.1
Flash Point, Cleveland Open Cup, °C, ASTM D92	225
Pour Point, °C, ASTM D97	-36

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2024

EXXONMOBIL LUBRICANTS & SPECIALTIES EUROPE, A DIVISION OF EXXONMOBIL PETROLEUM & CHEMICAL, BVBA (EMPC)

POLDERDIJKWEG

B-2030 Antwerpen

Belgium

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved