



Mobil Delvac Modern™ 15W-40 Complete Protection

Mobil Commercial Vehicle Lube , Mexico

Heavy Duty Engine Oil

Product Description

Mobil Delvac Modern 15W-40 Protección Completa is an oil designed to meet warranty requirements for high-speed, four-stroke heavy duty diesel engines. This product is formulated to maintain the durability of emission control systems, including diesel particulate filters and other advanced aftertreatment systems.

Fully backward compatible, Mobil Delvac Modern 15W-40 Protección Completa is suitable for both newer and older heavy duty engine designs. Accordingly, this oil meet or exceed the requirements of API CK-4, CJ-4, CI-4 PLUS, CI-4 service categories. Also approved by major original equipment manufacturers (OEM).

Features and Benefits

Mobil Delvac Modern 15W-40 Protección Completa is formulated with optimized base oil technology that provides up to an average of 80% more viscosity control¹ to help protect your equipment life.

1.Based on API CK-4 viscosity increase from Volvo T13 engine oil test.

Applications

- Recommended for heavy duty diesel applications including low emission engine designs and those featuring EGR.
- Recommended for heavy duty diesel applications using older and naturally aspirated conventional designs.

Specifications and Approvals

This product has the following approvals:
Detroit Detroit Fluids Specification 93K222
Detroit Fluids Specification 93K218
Mack EO-O Premium Plus
MACK EOS-4.5
RENAULT TRUCKS RLD-3
VOLVO VDS-4
VOLVO VDS-4.5
Cummins CES 20081
Cummins CES 20086

This product meets or exceeds the requirements of:
API CH-4
API CI-4 PLUS
API CJ-4
API CK-4
API CI-4
Caterpillar ECF-3

Properties and Specifications

Property	MOBIL DELVAC MODERN 15W-40 COMPLETE PROTECTION
Grade	SAE 15W-40

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2024
ExxonMobil Mexico, S.A. de C.V.
Poniente 146 No. 760 Col. Industrial Vallejo
C.P. 02300 Mexico, Ciudad de Mexico

(01 52) 55 5-333-9602 (01 52) 1-800-90-739-00

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil

Esso

XTO ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved