



## Vacmul EDM 3

Mobil Industrial , Malaysia

Multipurpose Electro Discharge Machining Fluids

### Product Description

Vacmul EDM 3 fluid is multipurpose dielectric fluid for use in all discharge machines working by penetration especially for roughing, finishing and superfinishing work. Vacmul EDM is very pure fluid designed for maximum machine productivity and operator comfort when used in electrical-discharge machining, also called spark-erosion machining. In this metalworking process metal is removed from a workpiece by applying a potential difference between the workpiece and a shaped electrode. Vacmul EDM has the ability to provide uniform insulation and then to permit controlled electrical discharge at the breakdown voltage.

Vacmul EDM 3 has the correct balance of viscosity, volatility, oxidation stability, heat transfer characteristics, low odour and low toxicity. Vacmul EDM 3 is a highly refined, narrow-cut, low viscosity fluid specially suited to finishing operations where a high quality finish is required. It functions as an insulator between tool and workpiece, spark conductor, coolant and as a flushing oil for chip removal. Vacmul EDM is recommended for roughing operations where a high metal removal rate is required and for finishing and superfinishing work.

### Features and Benefits

| Features  | Advantages and Potential Benefits                                |
|---|--|
| Highflash point                                     | Limits fire risk   |
| Excellent filterability through cartridge and earth | Increased production   |
| High wetability                                     | Ensures liquid / metal contact and fewer rejects                 |
| Bright, clean and odourless.                        | Easy viewing of work piece and fixtures                          |
| Low skin sensitivity in normal use                  | Easy handling and improved workshop environment                  |
| Non fatty compared to more viscous fluids.          | Higher metal removal rate and stable electrical discharge        |
| Good detergency with respect to small particles.    | Provides uniform insulation, higher precision and surface finish |

### Applications

- Excellent for all electro discharge machines that work by penetration.
- Especially suitable for roughing, finishing and superfinishing work.

### Typical Properties

| Vacmul EDM   | 3                |
|--|------------------|
| Density @ 15°C, kg/l ASTM D1298                    | 0.799            |
| Colour, Saybolt                                    | +30              |
| Viscosity cSt at 40°C mm <sup>2</sup> /s ASTM D445 | 2.37             |
| Flash Point, (P.M.) °C                             | 108              |
| IBP °C   | 243              |
| FBP °C   | 272              |
| Appearance   | Clear and Bright |

## Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design, and Vamul are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

05-2020


1-800-81-6233

SEALubeline@exxonmobil.com

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved