



Mobil 1™ 0W-20

Mobil Passenger Vehicle Lube , New Zealand

Ultimate Full Synthetic

Product Description

Mobil 1™ Triple Action Power+ is the ultimate full synthetic engine oil delivering outstanding engine Performance, Protection, and Cleanliness with the added benefit of Fuel Economy.

Features and Benefits

Why these matter for your engine:

- PERFORMANCE: Reduces the stress of daily wear and harsh conditions for longer engine life
- PROTECTION: Guards against extreme temperatures to prevent breakdowns
- CLEANLINESS: Prevents buildup of contaminants and sludge for a cleaner engine

Mobil 1™ Triple Action Power+ is feature packed to:

- PERFORM: Long lasting power
- PROTECT: 30X* better protection for high temperatures
- CLEAN: Prevents 99.9%** of the harmful acid contaminants that damage your engine
- PLUS: Increases engine efficiency for 8.4%*** improved fuel economy

*Based on Sequence IIIH, against API SP specification

**Based on TBN, against TAN in used oil

***Based on comparison of Sequence VIE against similar data of prior generation product recipe.

Applications

Mobil 1™ Triple Action Power+ is suitable for use in petrol, diesel, and hybrid vehicles.

Always check your owner's manual for the recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product is recommended for use in applications requiring:

FIAT 9.55535-CR1

This product meets or exceeds the requirements of:

Chrysler MS-6395

This product meets or exceeds the requirements of:

FORD WSS-M2C962-A1

API SP Resource Conserving

API SP

API SN PLUS

API SN

API SM

ILSAC GF-6A

ACEA C5

Properties and Specifications

Property	
Grade	SAE 0W-20
Mini-Rotary Viscometer, Apparent Viscosity, -40 C, mPa.s, ASTM D4684	13600
Pour Point, °C, ASTM D97	-48
Total Base Number, mgKOH/g, ASTM D2896	9.2
Ash, Sulfated, mass%, ASTM D874	0.76
Flash Point, Cleveland Open Cup, °C, ASTM D92	235
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	45
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10 ⁽⁶⁾ sec ⁽⁻¹⁾ , mPa.s, ASTM D4683	2.6
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	8.4
Density @ 15.6 C, g/ml, ASTM D4052	0.845
Viscosity Index, ASTM D2270	163

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2024

Mobil Oil New Zealand Limited

164-188 Beaumont St

Auckland

New Zealand

+ 64 4 498 4000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil Esso XTO
ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All
Rights Reserved