



Mobil Special™ 20W-50

Mobil Passenger Vehicle Lube, Hong Kong

高效能機油

產品說明

Mobil Special™ 20W-50 是適合所有車輛類型的高效能機油。Mobil Special 20W-50 為引擎提供了保護與潔淨。建議將 Mobil Special 20W-50 用於廣泛的應用和操作條件。

特色與效益

- 協助降低引擎磨損與腐蝕
- 協助保持引擎潔淨
- 複級油品, 在低溫情況下能夠更輕易發動
- 良好的高溫特性

規格與認證

此產品達到或超出以下要求:

API SL

特性及規格

| 特性 | |
|---|------------|
| 等級 | SAE 20W-50 |
| 總鹼值, mgKOH/g, ASTM D2896 | 5.5 |
| 黏度指數, ASTM D2270 | 130 |
| 150°C 條件下的高溫高剪切黏度, mPa.s, ASTM D4683 | 5.2 |
| 流動點, °C, ASTM D97 | -3 |
| 15°C 條件下的密度, g/ml, ASTM D4052 | 0.878 |
| 閃火點, °C, ASTM D92 | 230 |
| 硫酸鹽灰份, mass%, ASTM D874 | 0.8 |
| 40°C 下的運動黏度, mm ² /s, ASTM D445 | 185 |
| 100°C 下的運動黏度, mm ² /s, ASTM D445 | 20.5 |
| 微型旋轉黏度計, 表觀黏度, -20°C, mPa.s, ASTM D4684 | 25300 |

健康與安全

如需有關此產品的健康與安全建議，請參閱材料安全資料表 (MSDS)，其網址為：<http://www.msds.exxonmobil.com/psims/psims.aspx>

除非另有提及，否則此處使用的所有商標皆為 Exxon Mobil Corporation 或其子公司的商標或註冊商標。

09-2022

ExxonMobil Hong Kong
22nd Floor, Central Plaza,
18 Harbour Road, Wanchai
Hong Kong


+852 3197 8888

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved