



## Paving Asphalt C170 TPI

ExxonMobil Asphalt , Australia

Viscosity Graded Asphalt Product

### Product Description

Paving Asphalt C170 TPI is a viscosity graded asphalt product.

The specifications apply to those asphalt acquired for resale by ExxonMobil through purchase or exchange from third Party supplier.

### Applications

Paving Asphalt C170 TPI is recommended for road construction. If other applications are considered, then users should conduct appropriate testing before use.

### Properties and Specifications

Property	Limit	Standard Method(a)	
Dynamic Viscosity @ 60 C, Pa.s	Min-Max	ASTM D2171	140-200
Viscosity @ 135°C, Pa.s	Min-Max	ASTM D4402	0.25-0.45
Penetration, 25C, 100g, 5s, dmm	Min	ASTM D5	62
Flash Point, Cleveland Open Cup, °C	Min	ASTM D92	250
Matter Insoluble in Trichloroethylene, wt%	Max	ASTM D2042	1.0
Density @ 15 C, kg/m3	Min	ASTM D70	REPORT
Viscosity @ 60°C, on ASTM D6 residue, as percentage of original, %	Max	ASTM D2171	300

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2020

Energy lives here™

ExxonMobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved

