



## Mobilgard™ 540 AC

ExxonMobil Marine , Australia

High Performance Marine Diesel Engine Cylinder Oil

### Product Description

Mobilgard™ 540 AC by ExxonMobil is an MAN ES Category II approved, premium quality, high-performance marine diesel engine cylinder oil designed to effectively lubricate and deliver advanced cleanliness through effective deposit control across wide-ranging fuel and engine conditions.

Through the use of advanced formulation and detergency technologies in conjunction with a low Base Number (BN), Mobilgard 540 AC has demonstrated the ability to deliver advanced cleanliness and wear protection, whilst optimising cylinder oil feed-rates and effectively managing acid neutralisation in a range of engines and fuel applications.

Mobilgard 540 AC has been granted Category II status by MAN Energy Solutions. Its formulation has been designed for optimal lubrication at the elevated peak firing pressures and liner temperatures found in modern marine two stroke engines. The use of this product, in combination with the Mobil Serv<sup>SM</sup> Cylinder Condition Monitoring onboard monitoring, will help operators to achieve the best possible cylinder oil feed rates, while maintaining excellent lubrication.

This Category II cylinder oil is applicable for use in all MAN B and W two - stroke engines across LNG, Distillate and Very Low Sulphur Fuel Oil (VLSFOs) operation and recommended for engines Mark 9 and higher.

### Features and Benefits

Mobilgard 540 AC combines the use of high-quality, globally consistent base stocks with a superb additive formulation to provide superior detergency capability, which can lead to cleaner engine components.

Mobilgard 540 AC also offers outstanding resistance to oxidation, acid formation and excellent deposit control due to increased temperatures and pressures within combustion cylinders, which are particularly prevalent in LNG fuel operation.

### Applications

Mobilgard 540 AC is formulated to provide outstanding performance in marine crosshead engines operating on a wide variety of fuel applications, including continuous LNG use.

This Category II cylinder oil is applicable for all engines and recommended for MAN B&W two-stroke engines Mark 9 and higher.

### Specifications and Approvals

**This product has the following approvals:**

MAN Energy Solutions Copenhagen (Heritage MAN B&W) Category II for 2-Stroke Marine Engines

### Properties and Specifications

Property	
----------	--

Property	
Grade	SAE 50
Viscosity Index, ASTM D2270	99
Total Base Number, mgKOH/g, ASTM D2896	40
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	19
Pour Point, °C, ASTM D97	-30
Flash Point, Pensky-Martens Closed Cup, °C, ASTM D93	207
Density @ 15.6 C, kg/m <sup>3</sup> , ASTM D4052	904
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	218

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2022

Mobil Oil Australia Pty Ltd

A.B.N. 88 004 052 984

12 Riverside Quay


Southbank Vic 3006

+61 3 8633 8444

<http://www.exxonmobil.com>

Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

**ExxonMobil**



© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved