



Mobilgard™ 540 AC

ExxonMobil Marine , Bangladesh

High Performance Marine Diesel Engine Cylinder Oil

Product Description

Mobilgard™ 540 AC by ExxonMobil is an MAN ES Category II and WinGD Dual Fuel/LNG validated, premium quality, high-performance two-stroke marine diesel engine cylinder oil designed to effectively lubricate and deliver advanced cleanliness through effective deposit control across wide-ranging fuel and engine conditions.

Through the use of advanced formulation and detergency technologies in conjunction with a low Base Number (BN), Mobilgard 540 AC has demonstrated the ability to deliver advanced cleanliness and wear protection, whilst optimising cylinder oil feed-rates and effectively managing acid neutralisation in a range of engines and fuel applications.

Mobilgard 540 AC has been granted Category II status by MAN Energy Solutions and obtained Dual Fuel/LNG validation from Winterthur Gas & Diesel (WinGD). Its formulation has been designed for optimal lubrication at the elevated peak firing pressures and liner temperatures found in modern marine two-stroke engines. The use of this product, in combination with the MobilSM Cylinder Condition Monitoring service, can help operators monitor oil condition in real-time enabling them to optimize cylinder oil feed rates, while maintaining excellent lubrication.

This cylinder oil is applicable for use in:

- all MAN ES two-stroke engines operating on $\leq 0.50\%S$ fuels, LNG, ethane, methanol, and LPG.
- all WinGD, Wärtsilä and Sulzer two-stroke engines operating on $\leq 1.50\%S$ fuels, LNG and methanol.

Features and Benefits

Mobilgard 540 AC combines the use of high-quality, globally consistent base stocks with a superb additive formulation to provide superior detergency capability, which can lead to cleaner engine and exhaust system components.

Mobilgard 540 AC also offers outstanding resistance to oxidation, acid formation and excellent deposit control challenged from increased temperatures and pressures within combustion cylinders, which are particularly prevalent in LNG fuel operation.

Mobilgard™ 540 AC offers a single solution, helping vessel operators optimise their inventory and also gain access to a range of performance benefits.

Applications

Mobilgard 540 AC is formulated to provide outstanding performance in marine crosshead engines operating on a wide variety of fuel applications, including continuous LNG use.

This exceptional cylinder oil has been approved by MAN ES and WinGD for application to all their two-stroke engines operating on LNG, Methanol, Distillate and Very Low Sulphur Fuel Oil (VLSFOs).

Additionally it has received MAN ES approval for their two-stroke engines operating on ethane.

Specifications and Approvals

This product has the following approvals:

MAN Energy Solutions Copenhagen (Heritage MAN B&W) Category II for 2-Stroke Dual-Fuel Marine Engines (LNG, LPG, Methanol, ULSFO, VLSFO)

WinGD Ltd. Liquid Fuel General Usage for 2-Stroke Marine Engines according to manufacturer's latest operating guidelines

WinGD Ltd. LNG Validated for 2-Stroke Dual Fuel Marine Engines

WinGD Ltd. Methanol General Usage for 2-Stroke Dual Fuel Marine Engines

Properties and Specifications

Property	
Grade	SAE 50
Viscosity Index, ASTM D2270	99
Total Base Number, mgKOH/g, ASTM D2896	40
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	19
Pour Point, °C, ASTM D97	-30
Flash Point, Pensky-Martens Closed Cup, °C, ASTM D93	207
Density @ 15.6 C, kg/m ³ , ASTM D4052	910
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	218

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2024

ExxonMobil Marine Limited

Ermyn Way

Leatherhead, Surrey

United Kingdom KT22 8UX

<http://www.exxonmobil.com>

Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved