



Asphalt Blendstock

ExxonMobil Asphalt , Canada

Product Description

Asphalt Blendstock is derived from specially selected crude oils via carefully controlled refining processes.

The quality of ExxonMobil products is assured for every delivery. Products are manufactured according to global product integrity requirements.

Applications

Asphalt Blendstock is recommended for use in preparation of paving asphalt grades and some industrial applications.

Properties & Specifications

Asphalt Blendstock meets the following specification requirements:

Asphalt Property	Units	Method	Specification
Flash Point (C.O.C.)	°C	AASHTO T48	230 min

Above specifications may be subject to change.

Health & Safety

Detailed health and safety information for this product is provided in the Material Safety Data Sheet (MSDS), available upon request through your local representative or from www.imperial.com.

All trademarks used herein are trademarks of Exxon Mobil Corporation or one of its subsidiaries.

05-2020

Further Information

ExxonMobil supplies a full range of bitumen, waxes, white oils, process oils and a full range of other lubricants, fuels and chemical products worldwide. Please contact your local ExxonMobil representative, or contact us at www.imperial.com for more information on other products.

Every care has been taken in the preparation of this information. To the extent permitted by applicable law, all warranties and/or representations, express or implied, the accuracy of the information are disclaimed, and no liability is accepted for the accuracy or completeness of the same.

ExxonMobil

Exxon

Mobil

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved

