



Mobilgard™ 525

ExxonMobil Marine , Canada

Diesel Engine Cylinder Oil

Product Description

Mobilgard™ 525 is a marine diesel engine cylinder oil for crosshead engines running low and ultra low sulphur distillate fuels and meets the requirements of MAN and Wartsila engines. Designed to protect in extreme environments, Mobilgard 525 has an optimum viscosity of 20 cSt at 100°C and low volatility to ensure lubricant distribution and oil film retention and help protect engine parts.

Applications

- Combats the deposits and scuffing related engine wear associated with low sulphur fuels
- Excellent thermal and oxidative stability to ensure performance in a variety of engine conditions
- Formulated with detergent technology required to deliver excellent performance with low-sulphur fuel
- Detergency system provides strong control of piston groove deposits which is a critical area for distillate fuel operation
- Marine crosshead engines designed for increased power and fuel efficiency
- Earlier engine designs and engines in slow speed steaming operation

Specifications and Approvals

This product meets or exceeds the requirements of:

Winterthur Gas and Diesel Engine (Heritage Wartsila & Sulzer) 2-Stroke engines according to manufacturer's latest operating guidelines

Properties and Specifications

Property	
Grade	SAE 50
Flash Point, °C, ASTM D92	286
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	20
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	226
Pour Point, °C, ASTM D97	-9
Specific Gravity, 15 C/15 C, ASTM D4052	0.909
Total Base Number, mgKOH/g, ASTM D2896	25
Viscosity Index, ASTM D2270	102

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

02-2022

Imperial Oil

Petroleum and Chemicals Division

Lubricants and Specialties

240 Fourth Ave SW

C. P. 2480, Station M

Calgary AB T2P 3 M 9

1-800-268-3183

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil Esso XTO

© Copyright 2003-2022 Exxon Mobil Corporation. All Rights Reserved