



Mobilgard HSD 15W-40 CF-4

ExxonMobil Marine , 中国

Product Description

Mobilgard HSD 15W-40 CF-4 is a performance diesel engine oil that provides proven protection of diesel engines operating in marine service applications. Mobilgard HSD 15W-40 CF-4 is recommended by ExxonMobil for use in a wide range of diesel engines for use in a variety of operating environments in marine industries.

Features and Benefits

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Controls sludge build-up
TBN reserve	Deposit control
Component compatibility	Long seal and gasket life

Applications

Mobilgard HSD 15W-40 CH-4 is designed to provide proven engine protection for marine diesel engines, including those models typically used in industries such as Inland, coastal, fishing, dredging, offshore service and other similar applications.

Specifications and Approvals

This product is recommended for use in applications requiring:
API CF-4

Properties and Specifications

Property	
Grade	SAE 15W-40
Pour Point, °C, ASTM D97	-27
Viscosity Index, ASTM D2270	133
Density @ 15.6 C, g/ml, ASTM D4052	0.88
Total Base Number, mgKOH/g, ASTM D2896	6.1
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	15
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	117
Ash, Sulfated, mass%, ASTM D874	0.73

Property	
Flash Point, Cleveland Open Cup, °C, ASTM D92	234

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2022

ExxonMobil Marine Limited

Ermyn Way

Leatherhead, Surrey

United Kingdom KT22 8UX

<http://www.exxonmobil.com>

Due to continual product research and development, the information contained herein is subject to change without notification.

Typical Properties may vary slightly.

Energy lives here™

ExxonMobil

Exxon Mobil ESSO XTO

© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved