



## Flexxipave I-D

ExxonMobil Specialties , 中国

Flexxipave I-D is a polymer modified asphalt

### Product Description

Flexxipave I-D is recommended for road construction. If other applications are considered, then users should conduct appropriate testing before use.

### Application

Flexxipave I-D is recommended for road construction. If other applications are considered, then users should conduct appropriate testing before use.

### Properties and Specifications

Property	Min	Max
Penetration, 25C, 100g, 5s, 0.1mm, T0604	40	60
Softening Point, R&B, °C, T0606	60	
Ductility @5C, 5cm/min, cm, T0605	20	
Flash Point, °C, T0611	230	
Elastic Recovery, 25C, %, T0662	75	
Retained penetration ratio on RTFOT(T0610) Residue, 25C, %, T0604	65	
Ductility @5C on RTFOT(T0610) Residue, cm, T0605	15	

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2020

ExxonMobil Asia Pacific Ltd

1 HarbourFront Place

#06-00 HarbourFront Tower One

Singapore 098633


+65 6885 5000

<http://www.exxonmobil.com>

Every care has been taken in the preparation of this information. To the extent permitted by applicable law, all warranties and/or representations, express or implied, as to the accuracy of the information are disclaimed, and no liability is accepted for the accuracy or completeness of the same.

Energy lives here™

ExxonMobil



© Copyright 2003-2022 Exxon Mobil Corporation. All Rights Reserved