



Prowax 312

ExxonMobil Specialties , Finland

Product Description

Prowax 312 is a low-range melting point product in the Prowax line of petroleum slack and scale waxes. It is a translucent crystalline material in the solid state and a water white-to-straw yellow, clear liquid when molten. It is derived from petroleum via a carefully controlled refining process. Prowax 312 is comprised of a mixture of straight chain normal paraffin and branched, iso-paraffin hydrocarbons.

ExxonMobil waxes are produced and controlled according to the ExxonMobil Product Quality Management System, EN ISO 9000 or equivalent standard.

Applications

Prowax 312 can be used in the following applications subject to applicable laws and regulations in each jurisdiction*

- Candles
- Wax emulsions
- Wax blends

* User must check compliance with applicable regulations

Properties and Specifications

Property	Standard Method(a)	Min	Max
Melting Point, °C	ASTM D87	50.0	56.0
Oil Content, wt%	ASTM D721		6.0
ASTM Color by Auto Tristimulus	ASTM D6045		1.0
Kinematic Viscosity @ 100 C, mm ² /s	ASTM D445	2.7	4.1
Flash Point, Cleveland Open Cup, °C	ASTM D92	200	

Note 1: Products are certified on release to meet the values specified. Actual values may deviate within the established reproducibility of the test method specified.

Note 2: For purpose of determining conformance with specification, observed or calculated values shall be rounded off to the nearest unit in the last significant digit used in expressing the limiting value in accordance to the ASTM E 29 method

(a) In lieu of standard test method, alternate test methods may be used for the certification of a product property.

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2022

ExxonMobil Finland Oy Ab
PL 91 (Keilasatama 5)

02151 Espoo - FINLAND

<http://www.exxonmobil.com>

Koska tuotteita tutkitaan ja kehitetään jatkuvasti, voidaan tässä esitettyjä tietoja muuttaa ilman eri ilmoitusta. Tyypilliset ominaisuudet voivat vaihdella hieman. Kaikkia tuotteita ei ehkä ole paikallisesti saatavissa.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved