



Primol N 542
ExxonMobil Specialties , Hong Kong
Medicinal grade White Oil

Product Description

Primol N 542 is a purified mixture of liquid saturated hydrocarbons. It is a colourless, transparent oily liquid and is essentially odourless and tasteless. It is obtained from petroleum through several refining stages, including an ultimate purification by catalytic hydrogenation. Primol N 542 contains 5 ppm food-grade alpha-tocopherol (vitamin E) as an oxidation inhibitor.

Primol N 542 is manufactured to exceed the purity requirements of the Pharmacopoeias. Due to its superior chemical inertness, it demonstrates better color and oxidative stability than most mineral and vegetable oils, when stored and used under controlled conditions.

ExxonMobil White Oils are produced and controlled according to the ExxonMobil Product Quality Management System, EN ISO 9000 or equivalent standard.

Applications

Primol N 542 can be used in a variety of food-related, cosmetic and pharmaceutical applications subject to the applicable laws and regulations in each country (*).

Thermoplastics

Primol N 542 is recommended as a food packaging-grade plasticizer in Polystyrene. It offers an outstandingly low volatility but due to its high molecular weight, it is used in grades at relatively low oil content, in order to maintain transparency for General Purpose PS grades.

Primol N 542 is recommended for use as an external lubricant for non-plasticized PVC.

Elastomers and Adhesives

Primol N 542 is used for producing food-contact or medical rubber articles, such as EPDM or butyl rubber. Because of its extremely low volatility, it is particularly suited for the extension of Thermoplastic Elastomers when low fogging properties are required.

Primol N 542 is also recommended for Hot-Melt Adhesives formulations used in sanitary products.

(*) User must check compliance with applicable regulations.

Properties and Specifications

Primol N 542 meets the requirements of the following specifications:

- USA FDA, 21 CFR 178.3620(a), White Mineral Oil
- US Pharmacopeia, most recent edition, Mineral Oil
- National Sanitation Foundation (NSF), category H1, registration number 132493
- Europe Regulation (EU) 10/2011 on plastic material and articles intended to come into contact with foodstuff, White mineral oil

(*): Primol N 542 does not comply with the Liquid Paraffin definition of the European Pharmacopoeia due to the addition of an oxidation inhibitor and because of its viscosity.

CAS number: 8042-47-5
EINECS number: 232-455-8
INCI name (Europe): Paraffinum Liquidum
CTFA Dictionary name (USA): Mineral Oil

Typical values may vary within modest ranges and specifications may be subject to change.

| Property | Test Method | Typical | Min | Max |
|-----------------------------------|-------------|---------|-----------------------------|-----------------------------|
| Appearance | Visual | - | Clear and Bright | Clear and Bright |
| Odor | Olfactory | - | Odorless or almost odorless | Odorless or almost odorless |
| Color, Saybolt | ASTM D 6045 | - | + 30 | - |
| Kinematic Viscosity @ 40°C, mm²/s | ASTM D 445 | - | 90.0 | 110.0 |

| Property | Test Method | Typical | Min | Max |
|---|-------------|-------------|-------|-------|
| Kinematic Viscosity @ 100°C, mm²/s | ASTM D 445 | - | 11 | - |
| Density @ 15°C, kg/m³ | ASTM D 4052 | - | 866 | 876 |
| Relative Density @ 25°C/25° | ASTM D 4052 | - | 0.862 | 0.873 |
| Pour Point, °C | ASTM D 5950 | - | - | -12 |
| Flash Point, °C | ASTM D 92 | - | 250 | - |
| Refractive Index, nD²⁰ | ASTM D 1218 | - | 1.472 | 1.480 |
| Average Molecular Weight | ASTM D 2502 | - | 510 | - |
| Hydroc. with less than 25 carbons, wt % | ASTM D 6352 | - | - | 2 |
| Volatility @ 10 mm Hg, temp (°C) at which 2.5 % off | ASTM D 1160 | 299 | - | - |
| Volatility @ 10 mm Hg, temp (°C) at which 5 % off | ASTM D 1160 | 303 | 292 | - |
| Volatility @ 10 mm Hg, temp (°C) at which 10 % off | ASTM D 1160 | 308 | 302 | - |
| Carbon Type, % & Paraffinic / Naphthenic / Aromatic | AM-S | 69 / 31 / 0 | - | - |

Health and Safety

Detailed health and safety information for this product is provided in the Material Safety Data Sheet (MSDS), available upon request through your local representative or from www.ExxonMobil.com

Storage and Handling

Recommended storage and handling procedures for ExxonMobil white oil products are summarised in a separate bulletin available upon request through your local representative or from www.ExxonMobil.com

Further Information

ExxonMobil supplies a range of white oils, process oils, waxes, bitumen and a full range of other lubricants, fuels and chemical products worldwide. Please contact your local ExxonMobil representative, or contact us at www.ExxonMobil.com, for more information on other products.

The ExxonMobil logotype (and any other trademarks) are trademarks of Exxon Mobil Corporation or one of its subsidiaries.

05-2020
ExxonMobil Asia Pacific Ltd
1 HarbourFront Place
#06-00 HarbourFront Tower One
Singapore 098633

+65 6885 5000
<http://www.exxonmobil.com>

Every care has been taken in the preparation of this information. To the extent permitted by applicable law, all warranties and/or representations, express or implied, the accuracy of the information are disclaimed, and no liability is accepted for the accuracy or completeness of the same.

ExxonMobil

Exxon

Mobil

ESSO

XTL

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved