



PAVING ASPHALT 60/70 TPI

ExxonMobil Asphalt , Laos

PENETRATION GRADED ASPHALT PRODUCT

Product Description

Paving Asphalt 60/70 TPI is a penetration graded asphalt product. The specifications apply to those asphalt acquired for resale by ExxonMobil through purchase or exchange from third Party supplier.

Applications

Paving Asphalt 60/70 TPI is recommended for road construction. If other applications are considered, then users should conduct appropriate testing before use.

Properties and Specifications

Property	Standard Method(a)	Limit	
Penetration, 25 C, 0.1 mm	ASTM D5	Min-Max	60-80
Softening Point, °C	ASTM D36	Min	46
Flash Point, Cleveland Open Cup, °C	ASTM D92	Min	232
Solubility in Trichloroethylene, wt%	ASTM D2042	Min	99.0

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2020

Energy lives here™

ExxonMobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved

