



## AMERICAS SN 150 88 VI

ExxonMobil Basestocks , Mexico

ExxonMobil Basestocks

### Product Description

ExxonMobil AMERICAS SN 150 88 VI offers a wide span of properties and is used in the lubricant industry as diluent oil. With this selected product and the other base stock slates, ExxonMobil is the recognized market leader for Group I base stocks.

### Features and Benefits

AMERICAS SN 150 88 VI by ExxonMobil simplify our customers' operations thanks to its unique properties and to consistent quality following our proprietary Product Quality Management System (PQMS) standards. Benefits include:

- Unique stock tailored to diluent oil applications
- Superior supply chain/delivery logistics

### Specifications

Property	Limit	Standard Method(a)	
ASTM Color	Max	ASTM D1500	1.0
Sulfur, mass%	Max	ASTM D1552	0.3
Viscosity Index	Min	ASTM D2270	88
Distillation by GC, % off @ 371 C, %	Max	ASTM D2887	20
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s	Min-Max	ASTM D445	4.89-5.30
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s	Min-Max	ASTM D445	28.8-31.9
Water Content, mg/kg	Max	ASTM D6304	200
Flash Point, Cleveland Open Cup, °C	Min	ASTM D92	200
Flash Point, Pensky-Martens Closed Cup, °C	Min	ASTM D93	165
Pour Point, °C	Max	ASTM D97	-9
Appearance	Min-Max	Visual	Clear and Bright

Note 1: Products are certified on release to meet the values specified. Actual values may deviate within the established reproducibility of the test method specified.

Note 2: For purpose of determining conformance with specification, observed or calculated values shall be rounded off to the nearest unit in the last significant digit used in expressing the limiting value in accordance to the ASTM E 29 method

(a) In lieu of standard test method, alternate test methods may be used for the certification of a product property.

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2020

ExxonMobil Mexico, S.A. de C.V.

Poniente 146 No. 760 Col. Industrial Vallejo

C.P. 02300 Mexico, Ciudad de Mexico

<http://www.exxonmobil.com>

(01 52) 55 5-333-9602 (01 52) 1-800 90-739-00

All products may not be available in all countries. Every care has been taken in the preparation of this information. Typical values may vary within modest ranges and specifications may be subject to change. To the extent permitted by applicable law, all warranties and/or representations, express or implied, as to the accuracy of the information are disclaimed, and no liability is accepted for the accuracy or completeness of the same.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names which include Esso, Mobil, Exxon, or ExxonMobil. For convenience and simplicity, the term ExxonMobil may be used to represent all of these entities, and the products and services provided by those entities. Nothing in this brochure is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with local ExxonMobil-affiliated entities.

**ExxonMobil**

Exxon Mobil Esso XTO ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved