



## Mobilgard™ 570

ExxonMobil Marine , Mozambique

Diesel Engine Cylinder Oil

### Product Description

Mobilgard 570 by ExxonMobil is a premium quality, high-performance marine diesel engine cylinder oil. The outstanding performance of Mobilgard 570 has been demonstrated at the elevated peak firing pressures and liner temperatures found in modern marine two stroke engines. It has an optimum viscosity of over 20 cSt. at 100°C and low volatility to ensure excellent lubricant distribution and oil film retention. Through the use of a balanced formulation for all-round performance, Mobilgard 570 has demonstrated the ability to minimise cylinder oil feed-rates whilst showcasing excellent cleanliness under sustained operation with fuel Sulphur levels down to 1.5%.

### Features and Benefits

- Excellent thermal and oxidation stability can lead to reduced deposits and sludge formation.
- Outstanding detergency capability leads to potentially cleaner engine components
- Balanced formulation with low volatility can lead to lower feed rates and reduced cylinder oil consumption.

### Specifications and Approvals

<b>This product meets or exceeds the requirements of:</b>
MAN Energy Solutions Copenhagen (Heritage MAN B&W) 2-Stroke engines according to manufacturer's latest operating guidelines
Winterthur Gas and Diesel Engine (Heritage Wartsila & Sulzer) 2-Stroke engines according to manufacturer's latest operating guidelines

### Properties and Specifications

Property	
Grade	SAE 50
Density @ 15 C, kg/m3, ASTM D4052	0.938
Flash Point, Cleveland Open Cup, °C, ASTM D92	256
Pour Point, °C, ASTM D97	-9
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	222
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	20
Viscosity Index, ASTM D2270	104
Total Base Number, mgKOH/g, ASTM D2896	70

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2020

ExxonMobil Marine Limited  
Ermyn Way  
Leatherhead, Surrey  
United Kingdom KT22 8UX

<http://www.exxonmobil.com>

Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

Energy lives here™

**ExxonMobil**

Exxon Mobil  

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved