



## Mobilgard™ 450 NC

ExxonMobil Marine , Saudi Arabia

Diesel Engine Oil

### Product Description

Mobilgard™ 450 NC (No Chlorine) engine oil by ExxonMobil is a non-zinc and non-chlorine lubricant formulated with high-quality basestocks which provide low consumption characteristics, high-temperature oxidation resistance, and thermal stability. These basestocks are combined with specially selected stable additives resulting in an engine oil with well-balanced properties.

The detergent/dispersant qualities of Mobilgard 450 NC increases filter life and engine cleanliness. Its sustained high alkalinity provides excellent corrosion protection when using fuels containing up to 1.5 percent sulfur even though metals such as steel, copper, silver and bronze are present. Mobilgard 450 NC has outstanding lubricating properties and provides the necessary protection against corrosion.

Mobilgard 450 NC exhibits superior quality in reduced wear in piston rings and cylinder liners. It possesses good water separating ability.

### Features and Benefits

When used as recommended, Mobilgard 450 NC provides the following features and potential benefits:

Features	Advantages and Potential Benefits
High thermal and oxidation stability	Protects against sludge formation in intermittent marine service providing cleaner, smoother running engines
Effective anti-wear and load carrying properties	Protects critical wear surfaces and extends engine life
High TBN and Outstanding TBN Retention	Controls deposits and neutralizes acids produced in the combustion process
Excellent detergency/dispersancy	Controls carbon deposits and varnish formation which can lead to extended oil and filter life
Zinc-free	Protects silver bearings
Excellent water tolerance and separation	Can handle water contamination without additive depletion

### Applications

Mobilgard 450 NC engine oil has been specifically formulated to meet requirements of heavily loaded diesel engines manufactured by EMD and used in marine applications. It is suitable for other high horsepower marine diesel engines, or higher brake mean effective pressure (BMEP) using distillate fuels with a sulfur content up to 1.5 percent. It will lubricate such engines in drilling rigs and stationary power generation service as well. Mobilgard 450 NC has been approved by EMD and is recommended for diesel engines manufactured by Alco, Detroit Diesel (API CF-2) and Fairbanks Morse.

Mobilgard 450 NC engine oil meets the requirements of an SAE 40 grade marine diesel engine oil and is suitable wherever API CF and/or CF-2 performance is specified. It has quality recognition by EMD and excellent DD6V92 TA test results.

The absence of chlorine in Mobilgard 450 NC offers easier disposal. Waste-oil disposal costs of chlorine-containing lubricants are generally higher than those without.

**Properties and Specifications**

Property	
Grade	SAE 40
Ash, Sulfated, mass%, ASTM D874	1.6
Chlorine, ppm, ASTM D6443	50
Density @ 15 C, g/cm <sup>3</sup> , ASTM D4052	0.897
Flash Point, Cleveland Open Cup, °C, ASTM D92	260
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	14.1
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	139
Pour Point, °C, ASTM D97	-6
Total Base Number, mgKOH/g, ASTM D2896	13
Viscosity Index, ASTM D2270	98
Zinc, mg/kg, ASTM D5185	10

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2020

ExxonMobil Marine Limited  
 Ermyn Way  
 Leatherhead, Surrey  
 United Kingdom KT22 8UX

<http://www.exxonmobil.com>

Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

Energy lives here™

**ExxonMobil**

Exxon Mobil ESSO XTO ENERGY

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved