



## PAVING ASPHALT 60/70 TPI

ExxonMobil Asphalt, Singapore

PENETRATION GRADED ASPHALT PRODUCT

### Product Description

Paving Asphalt 60/70 TPI is a penetration graded asphalt product. The specifications apply to those asphalt acquired for resale by ExxonMobil through purchase or exchange from third Party supplier.

### Applications

Paving Asphalt 60/70 TPI is recommended for road construction. If other applications are considered, then users should conduct appropriate testing before use.

### Properties and Specifications

Property	Standard Method(a)	Limit	
Penetration, 25 C, 0.1 mm	ASTM D5	Min-Max	60-80
Softening Point, °C	ASTM D36	Min	46
Flash Point, Cleveland Open Cup, °C	ASTM D92	Min	232
Solubility in Trichloroethylene, wt%	ASTM D2042	Min	99.0

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2020

### Further Information

ExxonMobil supplies a full range of bitumen, waxes, white oils, process oils and a full range of other lubricants, fuels and chemical products worldwide. Please contact your local ExxonMobil representative, or contact us at [www.exxonmobil.com](http://www.exxonmobil.com) for more information on other products.

Every care has been taken in the preparation of this information. To the extent permitted by applicable law, all warranties and/or representations, express or implied, as to the accuracy of the information are disclaimed, and no liability is accepted for the accuracy or completeness of the same.



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved

