



## Mobilgard 5145

ExxonMobil Marine , Singapore

Marine Diesel Engine Cylinder Oil

### Product Description

Mobilgard™ 5145 by ExxonMobil is a premium quality, extra high performance, marine diesel engine cylinder oil. The outstanding performance of Mobilgard 5145 has been demonstrated at the elevated peak firing pressures and liner temperatures found in modern marine two stroke engines. It has an optimum viscosity of 20 cSt. at 100°C and low volatility to ensure excellent lubricant distribution and oil film retention. Mobilgard 5145 has demonstrated outstanding acid neutralisation capabilities, cleanliness and excellent ring and liner protection under sustained operation in highly corrosive engines under a variety of operating conditions, including slow steaming. Through the use of a balanced formulation, the high viscosity and low volatility is attained with little or no use of bright stock which can create deposit formation due to poor thermal stability.

### Features and Benefits

Features and Benefits

- Excellent corrosion protection in newer, more demanding engine types all operations, including slow steaming, leading to lower feed rates.
- Supreme thermal and oxidation stability can lead to reduced deposits and sludge formation. Cleaner engines can lead to reduced component wear rates.
- Exceptional anti-wear properties lead to potentially reduced liner and ring wear and excellent anti-scuffing control.
- Outstanding detergency capability leads to potentially cleaner pistons and liners and can help extend periods between overhauls.

### Properties and Specifications

Property	
Grade	SAE 50
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	20
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	210
Viscosity Index, ASTM D2270	105
Density @ 15 C, kg/m <sup>3</sup> , ASTM D4052	0.976
Pour Point, °C, ASTM D97	-24
Flash Point, Cleveland Open Cup, °C, ASTM D92	250
Total Base Number, mgKOH/g, ASTM D2896	145

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2020

ExxonMobil Marine Limited

Ermyn Way

Leatherhead, Surrey

United Kingdom KT22 8UX

<http://www.exxonmobil.com>

Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.

Energy lives here™

**ExxonMobil**

Exxon

Mobil



© Copyright 2003-2022 Exxon Mobil Corporation. All Rights Reserved