



ExxonMobil Residual Marine Fuel Oil (RMFO)

ExxonMobil Commercial Fuel , Chad

Product Description

EXXON MOBIL Corporation supplies marine fuels around the world through its dedicated ExxonMobil Marine Fuels (EMMF) division. Should you require information about the properties of fuel currently available in certain locations, please contact your EMMF representative, who will be able to help you.

You can be sure that the fuel you buy through EMMF meets stringent quality requirements, wherever it is delivered. To achieve this, EMMF supplies marine fuels that meet par specifications. These specifications apply to fuels produced by ExxonMobil, as well as to those fuels acquired for resale by EMMF through purchase or exchange from other sour

EMMF's specifications are reviewed regularly so that they incorporate the latest equipment and industry requirements, including the standards set by organisations such as AST ISO.

Specifications

Grade	RMA 10	RMB 30	RMD 80	RME 180	RMG 180	RMG 380	RMG 500	RMG 700	RMK 380	RMK 500	R 7
Viscosity @ 50 °C, cSt	10.00Max.	30.00 Max.	80.00 Max.	180.0 Max.	180.0 Max.	380.0 Max.	500.0 Max.	700.0 Max.	380.0 Max.	500.0 Max.	7
Density @ 15 °C, kg/m3	920.0Max.	960.0 Max.	975.0 Max.	991.0 Max.	991.0 Max.	991.0 Max.	991.0 Max.	991.0 Max.	1010.0Max.	1010.0Max.	10
CCAI, Calculated	850Max.	860M ax.	860M ax.	860M ax.	870M ax.	870M ax.	870M ax.	870M ax.	870M ax.	870M ax.	8
Sulphur, Mass %	Statutory Require ments										
Flash Point, °C	60.0 Min.	60.0 Min.	60.0 Min.	60.0 Min.	60.0 Min.	60.0 Min.	60.0 Min.	60.0 Min.	60.0 Min.	60.0 Min.	6
Hydrogen Sulphide, mg/kg	2.00 Max.	2.00 Max.	2.00 Max.	2.00 Max.	2.00 Max.	2.00 Max.	2.00 Max.	2.00 Max.	2.00 Max.	2.00 Max.	2
Acid Number, mg KOH/g	2.5 Max.	2.5 M ax.	2.5 M ax.	2.5 M ax.	2.5 M ax.	2.5 M ax.	2.5 M ax.	2.5 M ax.	2.5 M ax.	2.5 M ax.	2
Total Sediment, Aged, Mass %	0.10 Max.	0.10 Max.	0.10 Max.	0.10 Max.	0.10 Max.	0.10 Max.	0.10 Max.	0.10 Max.	0.10 Max.	0.10 Max.	0
Carbon Residue, Micro, Mass %	2.50Max.	10.00 Max.	14.00 Max.	15.00 Max.	18.00 Max.	18.00 Max.	18.00 Max.	18.00 Max.	20.00 Max.	20.00 Max.	2
Pour Point											
Winter Quality, °C	0Max.	0Max.	30 M ax.	30 M ax.	30Ma x.	30 M ax.	30 M ax.	30 M ax.	30Ma x.	30Ma x.	3
Summer Quality, °C	6Max.	6Max.	30Ma x.	30Ma x.	30Ma x.	30 M ax.	30Ma x.	30Ma x.	30Ma x.	30Ma x.	3
Water, Vol. %	0.30 Max.	0.50 Max.	0.50 Max.	0.50 Max.	0.50 Max.	0.50 Max.	0.50 Max.	0.50 Max.	0.50 Max.	0.50 Max.	0
Ash, Mass %	0.040Max.	0.070 Max.	0.070 Max.	0.070 Max.	0.100 Max.	0.100 Max.	0.100 Max.	0.100 Max.	0.150 Max.	0.150 Max.	0
Vanadium, mg/kg	50Max.	150 Max.	150 Max.	150M ax.	350M ax.	350M ax.	350M ax.	350M ax.	450M ax.	450 M ax.	4
Sodium, mg/kg	50 Max.	100 Max.	100 Max.	50 M ax.	100M ax.	100 Max.	100 Max.	100 Max.	100M ax.	100 M ax.	1
Aluminium + Silicon, mg/kg	25Max.	40 M ax.	40 M ax.	50 M ax.	60Ma x.	60 M ax.	60 M ax.	60 M ax.	60Ma x.	60 Ma x.	6
The fuel shall be free of used lubricating oil (ULO). A fuel shall be conside red to contain ULO if one of the following conditions is met:											

Grade	RMA 10	RMB 30	RMD 80	RME 180	RMG 180	RMG 380	RMG 500	RMG 700	RMK 380	RMK 500	R 7
Calcium + Zinc, mg/kg	Calcium > 30 and Zinc >15										
Calcium + Phosphorus, mg/kg	Calcium > 30 and Phosphorus > 15										

Health & Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided Material Safety Data Sheet (MSDS) are followed. MSDSs are available via the Internet at ExxonMobil.com. This product should not be used for purposes other than its intended

- MAIN HAZARD: FIRE
- Keep away from ignition sources.
- Discharge your static electricity before fueling.
- Fill portable containers on the ground.
- Handle/Transport in closed or properly vented containers and systems, consistent with all applicable laws.
- Harmful or fatal if swallowed.
- Avoid breathing the vapors and skin contact.
- Do not wash down spills with water. Prevent all spills from reaching water.

The Exxon logotype, the Running Tiger are trademarks of ExxonMobil Corporation, or one of its subsidiaries.

05-2020
Exxon Mobil Corporation
ExxonMobil House
Ermyn Way
Leatherhead
Surrey, UK KT22 8UX

800 662-4592

Due to continual product research and development, the information contained herein is subject to change without notification. Typical properties may vary slightly.

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved