



PAVING ASPHALT 60/70 TPI

ExxonMobil Asphalt , Thailand

PENETRATION GRADED ASPHALT PRODUCT

Product Description

Paving Asphalt 60/70 TPI is a penetration graded asphalt product. The specifications apply to those asphalt acquired for resale by ExxonMobil through purch exchange from third Party supplier.

Applications

Paving Asphalt 60/70 TPI is recommended for road construction. If other applications are considered, then users should conduct appropriate testing before use.

Properties and Specifications

Property	Standard Method(a)	Limit	
Penetration, 25 C, 0.1 mm	ASTM D5	Min-Max	60-80
Softening Point, °C	ASTM D36	Min	46
Flash Point, Cleveland Open Cup, °C	ASTM D92	Min	232
Solubility in Trichloroethylene, wt%	ASTM D2042	Min	99.0

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2020

Further Information

ExxonMobil supplies a full range of bitumen, waxes, white oils, process oils and a full range of other lubricants, fuels and chemical products worldwide. Please c your local ExxonMobil representative, or contact us at [www.exxonmobil.com](http://www.exxonmobil.com) for more information on other products.

Every care has been taken in the preparation of this information. To the extent permitted by applicable law, all warranties and/or representations, express or implic the accuracy of the information are disclaimed, and no liability is accepted for the accuracy or completeness of the same.

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved

