# ExonMobil

## PAVING ASPHALT AC 60/70

ExxonMobil Asphalt, Thailand

PENETRATION GRADED ASPHALT PRODUCT

### **Product Description**

Paving Asphalt AC 60/70 is a penetration graded asphalt product derived from specially selected crude oils via carefully controlled refining processes.

The quality of ExxonMobil products is assured for every delivery. They are produced and controlled according to the ExxonMobil Product Quality Management S EN ISO 9000 or equivalent standard.

# **Applications**

Paving Asphalt AC 60/70 is recommended for road construction. If other applications are considered, then users should conduct appropriate testing before use.

# **Properties & Specifications**

Paving Asphalt AC 60/70 meets DH-SP 401/2016specification requirements:

| Asphalt  | Unit          | Method      | AC 60/70 |
|--|---------------|-------------|----------|
| Penetration at 25° C, 100g, 5 sec                      | 0.1 mm        | ASTM D 5    | 60-70    |
| Softening Point  | °C            | ASTM D 36   | 45-55    |
| Ductility at 25° C, 5 cm/min (min)                     | cm            | ASTM D 113  | 100      |
| Flash Point COC (min)                                  | °C            | ASTM D 92   | 232      |
| Solubility in trichloroethylene (min)                  | wt %          | ASTM D 2042 | 99       |
| Dynamic Shear Rheology G*/sin δ, 10 rad/s @ 64oC (min) | kPa           | AASHTO T315 | 1.00     |
|  |               |             |          |
| Thin Film Oven Test at 163° C (ASTM D1754)             |               |             |          |
| Loss on heating (max)                                  | wt %          | ASTM D 1754 | 0.8      |
| Penetration of residue (min)                           | % of original | ASTM D 5    | 54       |
| Ductility of residue at 25° C , 5 cm/min (min)         | cm            | ASTM D 113  | 50       |

DH-SP 401/2016 specifications may be subject to change.

## Health & Safety

Detailed health and safety information for this product is provided in the Material Safety Data Sheet (MSDS), available upon request through your loca representative or from www.exxonmobil.com.

All trademarks used herein are trademarks of Exxon Mobil Corporation or one of its subsidiaries

06-2022

#### Further Information

ExxonMobil supplies a full range of bitumen, waxes, white oils, process oils and a full range of other lubricants, fuels and chemical products worldwide. Please c your local ExxonMobil representative, or contact us at www.exxonmobil.com for more information on other products.

Every care has been taken in the preparation of this information. To the extent permitted by applicable law, all warranties and/or representations, express or implied the accuracy of the information are disclaimed, and no liability is accepted for the accuracy or completeness of the same.

PAVING ASPHALT AC 60/70

