



Plastol 537

ExxonMobil Specialties , Thailand

Product Description

Plastol 537 is a paraffinic low-colour mineral oil, complying with the purity requirements defined by the United States Food and Drug Administration (FDA) in chapter 21 CFR 178.3620(c). Although less refined than other Plastol technical white oil grades, it has a markedly better colour and colour stability than conventional rubber process oils.

The quality of ExxonMobil White Oils is assured for every delivery. These products are produced and controlled according to the ExxonMobil Product Quality Management System, EN ISO 9000 or equivalent standard.

Applications

Elastomers

Plastol 537 is recommended as an extender oil in EPDM or EPDM-based Thermoplastic Olefinics (TPO) and Thermoplastic Vulcanisates (TPV). It provides improved stability against colour and mechanical degradation of EPDM bales during storage, when compared to conventional extender oils. Due to a much higher degree of refining leading to very low sulphur content, Plastol 537 is also well adapted to peroxide curing of EPDM or Thermoplastic Vulcanisates (EPDM).

Properties and Specifications

Plastol 537 meets the requirements of the following regulations:

USA FDA 21 CFR 178.3620(c), Mineral Oil

Typical values may vary within modest ranges and specifications may be subject to change.

Property	Test Method	Typical	Min	Max
----------	-------------	---------	-----	-----

Appearance	Visual		Clear and Bright	Clear and Bright
Colour, ASTM	ASTM D 1500	0.5		1.0
Kinematic Viscosity @ 40°C, mm ² /s	ASTM D 445		90.0	116.0
Kinematic Viscosity @ 100°C, mm ² /s	ASTM D 445	11.4		
Density @ 15°C, kg/m ³	ASTM D 4052	880		
Pour Point, °C	ASTM D 97			-3
Flash Point, °C	ASTM D 92		240	
Viscosity-Gravity Constant (VGC)	ASTM D 2501	0.809		
Volatility, wt % loss @163°C, 5hrs	ASTM D 6	0.15		
Sulphur content, wt %	ASTM D 4294			0.20
Carbon Type, %	ASTM D 2140			
Paraffinic		66		
Naphthenic		29		
Aromatic		5		

Health and Safety

Detailed health and safety information for this product is provided in the Material Safety Data Sheet (MSDS), available upon request through your local sales representative or from www.ExxonMobil.com

Further Information

ExxonMobil supplies a range of white oils, process oils, waxes, bitumen and a full range of other lubricants, fuels and chemical products worldwide. Please contact your local ExxonMobil representative, or contact us at www.ExxonMobil.com, for more information on other products.

The ExxonMobil logotype (and any other trademarks) are trademarks of Exxon Mobil Corporation or one of its subsidiaries.

05-2020

ExxonMobil Asia Pacific Ltd

1 HarbourFront Place

#06-00 HarbourFront Tower One

Singapore 098633

+65 6885 5000

<http://www.exxonmobil.com>

Every care has been taken in the preparation of this information. To the extent permitted by applicable law, all warranties and/or representations, express or implied, as to the accuracy of the information are disclaimed, and no liability is accepted for the accuracy or completeness of the same.

ExxonMobil

Exxon

Mobil



© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved