



AP/E SN 500

ExxonMobil Basestocks , Taiwan

Product Description

SN base stocks by ExxonMobil are designed to provide Group I base stocks in addition to the AP/E CORE Group I slate, offering broad blending coverage performance capabilities in a broad range of lubricant applications.

ExxonMobil's SN base stocks offer additional availability of Group I products, providing supply chain flexibility. ExxonMobil follows rigorous processes to ensure delivery of consistent quality base stocks so customers can be confident in their base stock supply.

Specifications and Properties

Property	Standard Method (a)	Units	Min.	Max.
Appearance	Visual	none	Clear and Bright	Clear and Bright
ASTM Colour	ASTM D1500	none		3.0
Kinematic viscosity at 40°C	ASTM D445	mm2/s	94	98
Viscosity Index	ASTM D2270	none	95	
Pour point	ASTM D97	°C		-6
Flash COC	ASTM D92	°C	237	

(a) In lieu of standard test method, alternate test methods may be used for the certification of a product property.

Note 1: Products are certified on release to meet the values specified. Actual values may deviate within the established reproducibility of the test method specified.

Note 2: For purpose of determining conformance with specification, observed or calculated values shall be rounded off to the nearest unit in the last significant digit in expressing the limiting value in accordance to the ASTM E 29 method.

Health and Safety

Detailed health and safety information for this product is provided in the material safety data sheet (MSDS), available upon request through your local sales representative or from www.ExxonMobil.com.

ExxonMobil and the ExxonMobil logotype are trademarks of Exxon Mobil Corporation or one of its subsidiaries.

05-2020
ExxonMobil
3225 Gallows Road
Fairfax, VA 22037-001

1-800-662-4592
<http://www.exxonmobil.com>

All products may not be available in all countries. Every care has been taken in the preparation of this information. Typical values may vary within modest ranges. Specifications may be subject to change. To the extent permitted by applicable law, all warranties and/or representations, express or implied, as to the accuracy of information are disclaimed, and no liability is accepted for the accuracy or completeness of the same.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names which include Esso, Mobil, Exxon, or ExxonMobil. For convenience and simplicity, the term ExxonMobil may be used to represent all of these entities, and the products and services provided by those entities. Nothing in this brochure is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with local ExxonMobil-affiliated entities.

ExxonMobil

Exxon

Mobil

Esso

XTD

© Copyright 2003-2024 Exxon Mobil Corporation. All rights reserved.

