



Americas SN 330

ExxonMobil Basestocks , United States

Product Description

SN 330 base stocks by ExxonMobil are designed to supplement the Americas CORE Group I slate, offering broad blending coverage with performance capabilities ranging from engine oils to industrial lubricants.

ExxonMobil's Americas SN 330 base stocks offer additional availability of Group I products, providing supply chain flexibility. ExxonMobil follows rigorous processes to ensure reliable delivery of consistent quality base stocks so customers can be confident in their base stock supply.

Sales Specifications

Americas SN			Americas 330
Property	Limit	Standard Method (a)	
Appearance		Visual	Band C
ASTM Colour	Max	ASTM D 1500	2.0
CCS Viscosity -10°C mPa•sec	Max	ASTM D 5293	2550
Flash Point, COC Deg C	Min	ASTM D 92	222
Kinematic Viscosity@ 40°C mm ² /sec	Min-Max	ASTM D 445	
Kinematic Viscosity@ 100°C mm ² /sec	Min-Max	ASTM D 445	7.90-8.55
NOACK Volatility wt%	Max	ASTM D 5800	9
Pour Point Deg C	Max	ASTM D 97	-9
Viscosity Index	Min	ASTM D 2270	95

(a) In lieu of standard test method, alternate test methods may be used for the certification of a product property.

Note 1: Products are certified on release to meet the values specified. Actual values may deviate within the established reproducibility of the test method specified.

Note 2: For purpose of determining conformance with specification, observed or calculated values shall be rounded off to the nearest unit in the last significant digit in expressing the limiting value in accordance to the ASTM E 29 method

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2020

Exxon Mobil Corporation
22777 Springwoods Village Parkway
Spring TX 77389

1-800-662-4592

<http://www.exxonmobil.com>

All products may not be available in all countries. Every care has been taken in the preparation of this information. Typical values may vary within modest ranges. Specifications may be subject to change. To the extent permitted by applicable law, all warranties and/or representations, express or implied, as to the accuracy of information are disclaimed, and no liability is accepted for the accuracy or completeness of the same.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names which include Esso, Mobil, Exxon, or ExxonMobil. For convenience and simplicity, the term ExxonMobil may be used to represent all of these entities, and the products and services provided by those entities. Nothing in this brochure is intended to overstate or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with local ExxonMobil-affiliated entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved