ExxonMobil

Americas SN 800

ExxonMobil Basestocks , United States

Product Description

ExxonMobil produces other specialized base stocks that offer a wide span of properties and are widely used in the lubricant industry. They are the workhorse ingredients for blenders of lubricants for many industrial applications. With these selected products and the other base stock slates, ExxonMobil is the recognized market leader for Group I base stocks. This Special Application base stock is available by available by rail, barge and vessel..

Features and Benefits

Consistent base stock formulations help simplify operations. This specialized base stock by ExxonMobil simplifies our customers' operations because we produce base stocks with consistent quality following our proprietary Product Quality Management System (PQMS) standards. Procurement and supply chain managers count on us to deliver the base stocks they need, when and where they need them. Benefits include:

- Unique stocks tailored to applications
- Consistence performance in formulations
- Superior supply chain/delivery logistics

Sales Specifications

Chem. & Phys. Property	UOM	Methods	Min.	Max.
Viscosity Index	none	ASTM D2270	90	
Kinematic Viscosity @ 40°C	mm2/s	ASTM D445	140	180
Flash Point, Cleveland Open Cup	°C	ASTM D92	246	
Pour Point	°C	ASTM D97		-6
Appearance	none	Visual	Clear and Bright	

Manufacturing Source: Americas

(a) Results referenced against standard method shown. Alternate methods may be used to certify value.
Note 1: Products are certified on release to meet the values specified. Actual values may deviate within the established reproducibility of the test method specified.
Note 2: For purpose of determining conformance with specification, observed or calculated values shall be rounded off to the nearest unit in the last significant digit used in expressing the limiting value in accordance to the ASTM E 29 method

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims/psims.aspx

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

02-2024
Exxon Mobil Corporation
22777 Springwoods Village Parkway
Spring TX 77389

1-800-662-4592

http://www.exxonmobil.com

All products may not be available in all countries. Every care has been taken in the preparation of this information. Typical values may vary within modest ranges and specifications may be subject to change. To the extent permitted by applicable law, all warranties and/or representations, express or implied, as to the accuracy of the information are disclaimed, and no liability is accepted for the accuracy or completeness of the same.

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names which include Esso, Mobil, Exxon, or ExxonMobil. For convenience and simplicity, the term ExxonMobil may be used to represent all of these entities, and the products and services provided by those entities. Nothing in this brochure is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with local ExxonMobil-affiliated entities.

ExxonMobil

Exxon Mobil Esso XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved