



MOBIL DELVAC MODERN 10W-40 FULL PROTECTION

Mobil Commercial Vehicle Lube , Argentina

Mobil commercial-vehicle-lube

Product Description

MOBIL DELVAC MODERN 10W-40 FULL PROTECTION is an extra high performance synthetic technology diesel engine oil that helps extend engine life in the severe on and off-highway applications while delivering outstanding performance in modern, high-output, low-emission engines including those with Exhaust Recirculation (EGR) and Aftertreatment Systems with Diesel Particulate Filters (DPFs) and Diesel Oxidation Catalysts (DOCs). Fully backwards compatible, MOBIL DELVAC MODERN 10W-40 FULL PROTECTION will also deliver the same exceptional performance in older conventional engines. It meets or exceeds the requirements of the API CK-4, CJ-4 service categories as well as key Original Equipment Manufacturer (OEM) requirements.

Features and Benefits

MOBIL DELVAC MODERN 10W-40 FULL PROTECTION is formulated using synthetic technology and a detergent system to deliver excellent performance in both new and older engines. In addition to assuring excellent control of oil thickening due to soot build-up and TBN retention for long drain intervals, MOBIL DELVAC MODERN 10W-40 FULL PROTECTION advanced technology also provides outstanding resistance to oil consumption, oxidation, corrosive and abrasive wear, and high temperature deposits.

Features	Advantages and Potential Benefits
Excellent soot-viscosity control	Helps to maintain engine efficiency, long engine life and long oil life
Outstanding thermal and oxidative stability	Helps to reduce low temperature sludge build-up and high temperature deposits
Excellent oil consumption control	Helps to lower oil costs due to less make-up oil during operation
Excellent TBN reserves	Helps to improve corrosion protection and to extend drain intervals
Stay-in-grade shear stability	Helps to maintain viscosity in severe, high temperature service for greater wear protection and long engine life
Excellent low temperature pumpability	Fast oil flow and helps to reduce wear during engine start-up in low temperatures
Excellent resistance to corrosive and abrasive wear	Long life of critical wear surfaces
Component compatibility	Long gasket, seal, and after treatment (DPF and DOC) life

Applications

Recommended by ExxonMobil for use in:

- Heavy Duty Diesel Engines including Euro V/VI and China V/VI(1) modern low emissions vehicles, utilizing technologies such as Diesel Particulate Filter (DPF), Selective Catalytic Reduction (SCR), Continuously Regenerating Traps (CRT), Diesel Oxidation Catalysts (DOC) and Exhaust Gas Recirculation (EGR).
- High-performance diesel applications including turbo-charged designs featuring EGR Technology and diesel applications using older, naturally aspirated conventional designs.
- On-highway heavy-duty trucking and off-highway including: construction, mining, quarrying, and agriculture.

Specifications and Approvals

This product has the following approvals:
Detroit Detroit Fluids Specification 93K222

<b>This product has the following approvals:</b>
Detroit Fluids Specification 93K218
MACK EOS-4.5
RENAULT TRUCKS RLD-3
VOLVO VDS-4.5
MAN M 3775
Ford WSS-M2C171-F1
MB-Approval 228.31
MTU Oil Category 2.1

<b>This product is recommended for use in applications requiring:</b>
MAN M 3575

<b>This product meets or exceeds the requirements of:</b>
API CJ-4
API CK-4
API SN
ACEA E7
ACEA E9
Caterpillar ECF-3
Cummins CES 20086
Cummins CES 20081

Properties and Specifications

Property	
Grade	SAE 10W-40
Viscosity Index, ASTM D2270	158
Total Base Number, mgKOH/g, ASTM D2896	10
Pour Point, °C, ASTM D97	-48
Noack Volatility, mass%, ASTM D5800	10
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	14.11
Flash Point, Cleveland Open Cup, °C, ASTM D92	219

Property	
Density @ 15.6 C, g/ml, ASTM D1298	0.862
Ash, Sulfated, mass%, ASTM D874	0.69
Appearance, AMS 1738	Clear and Bright

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2023

Cosan Lubricantes S.R.L.

Av. Libertador 6343, Piso 8

CABA, CP 1498, Buenos Aires – Argentina

0800 345 79540

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect pro performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without nc All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com) ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intende override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved