



## DIOL™ 9 RF 20W40

Mobil Commercial Vehicle Lube , Argentina

Railroad Crankcase Oil

### Product Description

DIOL™ 9 RF 20W40 is a premium heavy-duty crankcase lubricant for locomotive diesel engines. This product is designed to meet the severe service demands imposed by the latest railroad diesel locomotive engines.

### Features and Benefits

- Zinc Free - Excellent Silver Bearing Lubricity
- Enhanced Oxidation, Sludge-Soot Handling and Viscosity Control
- Excellent Deposit, Corrosion and Wear Control
- Formulated for use with low sulfur and ultra-low sulfur diesel fuels
- Extended oil drain intervals and high locomotive utilization rates
- Chlorine Free

### Applications

DIOL™ 9 RF 20W40 oil is formulated for LMOA Generation 6 applications with an engine manufacturer endorsed additive package.

### Specifications and Approvals

#### This product has the following approvals:

LMOA Gen 6 - Full Approval (letter on file)

### Properties and Specifications

| Property                                                   |            |
|------------------------------------------------------------|------------|
| Grade                                                      | SAE 20W-40 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92              | 200        |
| Viscosity Index, ASTM D2270                                | 108        |
| Pour Point, °C, ASTM D97                                   | -15        |
| Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445 | 16         |
| Base Number, mgKOH/g, ASTM D2896                           | 9          |

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2021

Cosan Lubricantes S.R.L.

Av. Libertador 6343, Piso 8


CABA, CP 1498, Buenos Aires – Argentina

0800 345 79540

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved