



MOBIL DELVAC LEGEND 1200 SERIES

Mobil Commercial Vehicle Lube , Argentina

Heavy Duty Diesel Engine Oils

Product Description

Mobil Delvac Legend 1230, 1240, and 1250 are heavy duty, diesel engine oils formulated from high performance base oils and a balanced additive system of ashless dispersants, metallic detergents, and inhibitors to control oxidation, wear, corrosion, and rust. They are used in a wide range of applications where a monograde lubricant is recommended including 2-cycle diesel applications (e.g. the Detroit Diesel's Series 53, 71, 92, and 149 two cycle engines).

Features and Benefits

Features	Advantages and Potential Benefits
Excellent oxidation and thermal stability	Keeps engines clean and extends oil life
Good rust and corrosion prevention	Long engine and component life

Applications

- Diesel powered equipment including 2-cycle applications
- On highway light and heavy duty trucking.
- Off highway industries including: construction, mining, quarrying, and agriculture.
- Mobil Delvac 1230 is suitable for use in lawn mowers. *
- Certain transmissions requiring an API CD oil. *

* Please refer to owners manual.

Specifications and Approvals

This product is recommended for use in applications requiring:	MOBIL DELVAC LEGEND 1230	MOBIL DELVAC LEGEND 1240	MOBIL DELVAC LEGEND 1250
API CD	X	X	X

Properties and Specifications

Property	MOBIL DELVAC LEGEND 1230	MOBIL DELVAC LEGEND 1240	MOBIL DELVAC LEGEND 1250
Grade	SAE 30	SAE 40	SAE 50
Appearance, AMS 1738	Clear and Bright	Clear and Bright	Clear and Bright
Density @ 15 C, g/ml, ASTM D4052	0.8808	0.8868	0.8993
Flash Point, Cleveland Open Cup, °C, ASTM D92	249	259	265
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	11.7	15.6	19.5

Property	MOBIL DELVAC LEGEND 1230	MOBIL DELVAC LEGEND 1240	MOBIL DELVAC LEGEND 1250
Pour Point, °C, ASTM D97	-24	-24	-15
Viscosity Index, ASTM D2270	102	99	99

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2022

Cosan Lubricantes S.R.L.

Av. Libertador 6343, Piso 8

CABA, CP 1498, Buenos Aires – Argentina

0800 345 79540

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil Esso XTO

© Copyright 2003-2022 Exxon Mobil Corporation. All Rights Reserved