



Wyrol HS

Mobil Industrial , Austria

Hydraulic Oil

Product Description

Wyrol HS oils are premium synthetic, low staining, low gum-forming, anti-wear hydraulic fluids that are specifically designed for use in modern aluminium rolling mills. They are designed to meet the most up-to-date requirements of high productivity aluminium cold rolling mills. Leakage of conventional hydraulic fluids leads to contamination of the aluminium rolling oil system; this may cause staining and gum formation on finished metal surfaces. However, contamination of the roll oil with Wyrol HS significantly reduces this effect. Wyrol HS has good anti-wear properties, excellent oxidation stability and good protection against rust and corrosion. Although Wyrol HS is a synthetic product, it is miscible with mineral oil, so change over from conventional hydraulic oil to Wyrol HS can be achieved with relative ease. Due to the nature of the base oil, Wyrol HS does not meet U.S. FDA Regulation 21 CFR 178.3910(a). If this is required, Wyrol H should be used.

Features and Benefits

Wyrol HS are high performance synthetic hydraulic fluids, which exhibit very low staining characteristics reducing the potential of production material rejects. Their excellent oxidation stability and good anti-wear protection properties result in longer oil life and improved hydraulic component performance.

Wyrol HS oils offer the following benefits:

- Low staining characteristics reduce the potential of production rejects
- Good anti-wear properties reduce hydraulic system component wear and extend service life
- Excellent oxidation stability minimises system deposits and improves oil life, reducing maintenance costs

Applications

- Hydraulic systems in aluminium cold rolling mills
- Suitable for use in low and high pressure hydraulic systems
- Recommended for gear, vane and piston pumps in hydraulic applications

Typical Properties

| Wyrol HS | 22 | 46 |
|---|------|------|
| Density at 15 °C, kg/m ³ , ASTM D 4052 | 868 | 870 |
| Kinematic Viscosity at 40°C, mm ² /s, ISO 3104 | 22 | 44 |
| Kinematic Viscosity at 100 °C, mm ² /s, ISO 3104 | 3.7 | 5.3 |
| Pour Point, °C, ISO 3016 | -51 | -42 |
| Flash Point, COC, °C, ISO 2592 | 160 | 175 |
| Copper Corrosion, 3h, 100°C, rating, ISO 2160 | 1 | 1 |
| Rust Prevention, distilled water, ISO 7120 | Pass | Pass |

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype and the Pegasus design are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

11-2019

ExxonMobil Lubricants & Specialties Europe, division of ExxonMobil Petroleum & Chemicals BVBA.

This information relates only to products supplied in Europe (including Turkey) and the Former Soviet Union.

EXXONMOBIL LUBRICANTS & SPECIALTIES EUROPE, A DIVISION OF EXXONMOBIL PETROLEUM & CHEMICAL, BVBA (EMPC)

POLDERDIJKWEG

B-2030 Antwerpen

Belgium

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil

Esso

XTO
ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved