



**MOBIL DELVAC LEGEND 1300 SERIES**

Mobil Commercial Vehicle Lube , Australia

Monograde High Performance Diesel Engine Oil

**Product Description**

Mobil Delvac Legend 1330, 1340 and 1350 are high performance, monograde diesel engine oils formulated from advanced technology base oils and a balanced additive system. They are specifically engineered for performance in intercooled, turbo-charged engines operating under severe on and off highway conditions. Mobil Delvac Legend 1300 monogrades are used in a wide range of applications where a monograde lubricant is recommended.

These products are fully compatible with Mobil Delvac 1330/1340/1350 and can be used as a replacement of same.

**Features and Benefits**

Features	Advantages and Potential Benefits
Excellent protection against oil thickening, high temperature deposits, sludge build-up, oil degradation and corrosion	Long engine life Wear protection Excellent protection against ring sticking
TBN reserve	Long-term deposit/wear control

**Applications**

- Naturally aspirated and turbo-charged diesel powered equipment
- On highway light and heavy duty trucking
- Off highway industries including: construction, mining, quarrying, and agriculture

**Specifications and Approvals**

This product is recommended for use in applications requiring:	MOBIL DELVAC LEGEND 1330	MOBIL DELVAC LEGEND 1340	MOBIL DELVAC LEGEND 1350
API CF	X	X	X
API CF-2	X	X	X
API SF	X	X	X

**Properties and Specifications**

Property	MOBIL DELVAC LEGEND 1330	MOBIL DELVAC LEGEND 1340	MOBIL DELVAC LEGEND 1350
Grade	SAE 30	SAE 40	SAE 50

Property	MOBIL DELVAC LEGEND 1330	MOBIL DELVAC LEGEND 1340	MOBIL DELVAC LEGEND 1350
Ash, Sulfated, mass%, ASTM D874	1	1	1
Density @ 15 C, g/ml, ASTM D1298	0.892	0.897	0.901
Flash Point, Cleveland Open Cup, °C, ASTM D92	243	271	267
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	11.2	15.1	19.5
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	94.4	152	224
Pour Point, °C, ASTM D97	-33	-27	-21
Total Base Number, mgKOH/g, ASTM D2896	9	9	9
Viscosity Index, ASTM D2270	105	99	99

### Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2022

Mobil Oil Australia Pty Ltd

A.B.N. 88 004 052 984

12 Riverside Quay

Southbank Vic 3006

+61 3 8633 8444

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**



© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved